

Produktion

- Can be used for chocolate and Procusini® mini 3D Choco Refills
- Technology layer-by-layer build-up of food
- Stainless steel cartridge heatable
- Usable volume 15 ml
- Positioning accuracy 0,1 mm
- Nozzle diameter 1,0 mm
- Production speed 5 – 50 mm/s
- Movement speed 5 – 200 mm/s
- Usable production area 90 x 90 x 46 mm

Dimensions and weights

- Outer dimensions unit length: 235 mm
width: 250 mm
height: 275 mm
- Shipping carton 350 x 350 x 350 mm (L x W x H)
- Weight unit 4 kg
- Delivery weight 6 kg

Temperatures

- Ambient temperature 20 - 22 °C
- Storage temperature 0 - 32 °C
- Heatable stainless steel cartridge 20 - 40 °C

Power supply

- Power supply unit (AC) 100-240 VAC; 50 – 60 Hz
- Power (DC) 12 V; 5 A, 60 W
- Protection Short circuit/overload/overvoltage/temperature

Software

- Procusini® Club online platform with templates and applications for creating own print templates
- Compatibility Google Chrome (browser based)
- File formats STL, JPG

Operation and setting options

- User interface on the unit 3,5 Zoll TFT-Touch-Display, 5 languages
- Data transfer SD-card
- Adjustment options preheating temperature, printing temperature, flow rate and printing speed

