

# SURF X™ PRO 2000

## Gun Flush



### Keep Your Gun CLEAN, GREEN and MEAN with SURF X™ PRO 2000 Gun Flush

**SURF X™ PRO 2000 Gun Flush** is an environmentally sensible flushing liquid for all spray guns that Spray Foam, Resin, Paint and coatings. Use this daily to keep your gun mix chamber clean and clear, allowing you to spray smoothly and evenly throughout the day.

**SURF X™ PRO 2000 Gun Flush** delivers improved productivity and performance all day by flushing build-up of foam, liquid or hardened Isocyanates, Polyol Coatings (Polyurea), Silicon, Resin (Epoxy, Polyester, and Vinyl Ester) and Adhesives.

Supplied in 32 oz. (Quart) Clear HDPE Plastic Boston Round Bottle with an Easy Pour Push Pull Cap.



#### ENVIRONMENTAL

- ☐ Reduced VOC
- ☐ Non-Hazardous
- ☐ Non-Flammable
- ☐ Non-Toxic
- ☐ DOES NOT contain raw materials known to the State of California (Prop 65) to cause cancer, birth defects or other reproductive harm
- ☐ DOES NOT contain raw materials on the NJ Community Right to Know Environmental Hazardous Substance (EHS) List
- ☐ DOES NOT contain raw materials listed on SECTION 12(b) of HAPs List
- ☐ No SARA 313 Ingredients
- ☐ REACH Compliant

#### Directions:

- ☐ Turn off both A and B lines.
  - ☐ Insert the canister with **SURF X™ PRO 2000 Gun Flush** into the gun.
  - ☐ Pull the trigger several times to prime **SURF X™ PRO 2000 Gun Flush** into the pump.
  - ☐ Spray onto cardboard to see **SURF X™ PRO 2000 Gun Flush** released into the gun mix chamber and build-up dissolved.
  - ☐ Turn on both A and B lines and squeeze the trigger until you see **SURF X™ PRO 2000 Gun Flush** spraying out of the gun.
  - ☐ You are now ready to continue spraying.
  - ☐ Repeat this when you see an uneven spray pattern or want to clean your gun.
- This will keep your gun chamber clean and prepared for subsequent use.

**RECOMMENDED MATERIALS TO USE FOR:  
O-Rings, Gaskets, Hoses and Pump Packaging**

**MATERIAL TO AVOID**

Teflon	Mild Steel	Polyethylene	Viton	Phenolic	PET	Noryl EN-265	Lucite
Butyl Rubber	Halar	Polypropylene	ABS	Polyurethane	Lexan	Noryl -731	Hypalon
Silicon Rubber	Melamine	Ryton	Durel	PVC	Valox	Polysulfone	
Klarez	Nylon 101		Kynar	Buna-N	Polyester	Ultem	

**TYPICAL PROPERTIES**

Appearance:	Clear Liquid
Flash Point: (Pensky-Martens closed cup)	169 °F
Odor:	Mild Organic Ester
Surface Tension:	24 (dynes/cm 24) (water = 1.0)
pH (50% solution in water @ 68°F)	6.8 - 7.8
Vapor Pressure: (components)	0.20 - 0.90 mmHg @ 20 °C (68 °F)
Initial boiling point/ boiling range (@ 760 [mm Hg])	356 - 396 °F
Ideal Operating Temp (°F)	Room Temperature or maximum heated to 140 °F
Ideal Operating Concentration	Full Strength
Specific Gravity @ (68°F)	0.980 - 0.984
Weight/Gal. (lbs. /gal.)	8.20
VOC Content: (ASTM D-2369, Method 24)	3.85 lbs./gal or 437 grams/liter
HMIS Rating:	Health = 2 Fire = 2 Reactivity = 0
Product #	02-W189569

**SAFETY & HANDLING PRECAUTIONS**

Refer to SDS for additional safe handling & disposal

**Direct contact of SURF X™ PRO 2000 Gun Flush will cause a mild skin irritation or serious eye irritation.** It is important to utilize recommended gloves (natural rubber), safety goggles and other suitable protective clothing your company recommends. Aspiration hazard if swallowed. Keep liquid and vapor away from heat, sparks and flames. Keep container closed. **Use product with adequate ventilation.**

**Do Not take internally.** Keep out of reach of children. Avoid contact with skin, eyes and clothing. Avoid breathing vapors or mist. Wash thoroughly after handling. Never give anything by mouth to an unconscious person. Get medical advice/attention.

**Refer to SDS Section 4 First Aid Measures**

**DISPOSAL**

Refer to SDS for additional safe handling & disposal

**The spent material should not be disposed of in any sewerage system.** Solutions containing hazardous or non-hazardous coatings and other soils should be handled and treated according to Federal, State and Local Environmental Laws. Discharge your waste and rinse water according to Federal, State and Local Regulations.

**PACKAGING**

**32 oz. Clear HDPE Plastic Boston Round Bottle with an EasyPour Push Pull Cap.**

**Case of 6 or 36 Quarts (32 oz. each)**

This product should be kept in its original container above freezing and less than 100 °F. Store in a dry area.



10 Eagle Avenue - Suite 500 - Mount Holly, NJ 08060  
Phone: 609-518-7577 / Fax: 609-518-5277