essentials™

Product Code: CLo36

Technical Specification

Luckinslive 389086428

Description: 13A 2 Gang Double Pole Switched Socket Outlet





General Information

Dimensions (mm) 140 (W) x 80 (H) x 42 (D)

Plate Fixing Centres - Horizontal (mm) 120.6

> Colour Grey Insert Colour

> > Materials Front Plate & Mounting Box:

Electrophoretically Coated Steel

Rear Housing: Urea

Terminal Screws: Steel & Yellow Passivated

Operating Voltage (AC)

Resistive Load Rating (A) 13 Termination Type Screw

Terminal Size (mm) Ø5

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Double Pole Switch Twin Earth Terminals Supplied Back Box Depth (mm)

Back Box Knockouts - Total (mm) 7 x Ø20 Back Box Knockouts - Top (mm) 3 x Ø20

Back Box Knockouts - Rear (mm) None Back Box Earth Terminal Supplied

Ingress Protection IP20 Operational Temperature (°C) -5 to +40 Warranty (Years)

Standards BS 1363-2

Style Metal Clad

Insert & Rocker Switch: Urea Terminals: Brass

Contacts: Silver "on-lay" Copper / Brass

Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel

Frequency (Hz) 50

Terminal Torque Value (Nm) 2

Back Box Knockouts - Bottom (mm) 2 x Ø20

Back Box Knockouts - Sides (mm) 1 x Ø20

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal











Specification is subject to change without notice. Errors & Omissions excluded.