

4-Channel POTS 2-Wire FXO/FXS to Fiber Converter Installation Kits (with RS-485 Data) Selector Guide



Model	FXO (Exchange)	FXS (Subscriber)	Function	Fiber	Installation	Distance Capability*
PK4DM	1	1	POTS	MM Duplex	Standalone	2 km
PK4DM-RM	1	1	POTS	MM Duplex	Rack-Mount	2 km
PKR4DM	-	2	Ring Down	MM Duplex	Standalone	2 km
PKR4DM-RM	-	2	Ring Down	MM Duplex	Rack-Mount	2 km
PK4DMSF	1	1	POTS	MM Simplex	Standalone	2 km
PK4DMSF-RM	1	1	POTS	MM Simplex	Rack-Mount	2 km
PKR4DMSF	-	2	Ring Down	MM Simplex	Standalone	2 km
PKR4DMSF-RM	-	2	Ring Down	MM Simplex	Rack-Mount	2 km
PK4DS	1	1	POTS	SM Duplex	Standalone	20 km
PK4DS-RM	1	1	POTS	SM Duplex	Rack-Mount	20 km
PKR4DS	-	2	Ring Down	SM Duplex	Standalone	20 km
PKR4DS-RM	-	2	Ring Down	SM Duplex	Rack-Mount	20 km
PK4DSSF	1	1	POTS	SM Simplex	Standalone	20 km
PK4DSSF-RM	1	1	POTS	SM Simplex	Rack-Mount	20 km
PKR4DSSF	-	2	Ring Down	SM Simplex	Standalone	20 km
PKR4DSSF-RM	-	2	Ring Down	SM Simplex	Rack-Mount	20 km

NOTES:

1. All units have LC optical connectors.
2. "-RM" indicates Rack-Mount.
3. Rack-Mount kits include one 2-Slot chassis and one standalone enclosure.
4. All units support RS-485 data up to 64Kbps.

* Requires appropriate length of fiber optic cable.

VERSITRON, Inc.

83 Albe Drive • Suite C • Newark, DE 19702

Tel: 302-894-0699

Fax: 302-894-0624

Toll Free: 800-537-2296

www.versitron.com