

# 6-Port 10/100/1000 Web Smart Switch with (1) SFP Slot

SG70660M

## Technical Specifications

<b>Standards:</b>	IEEE 802.3, 802.3ab, 802.3u, 802.3x, 802.1Q
<b>Network Ports:</b>	(5) 10/100/1000Mbps Copper Ports (RJ-45) (1) 100/1000Mbps SFP Slot
<b>Copper Ports:</b>	Shielded RJ-45, 10/100Mbps, auto-negotiation, auto-MDI/MDI-X
<b>Fiber Port:</b>	Supports 100/1000Mbps SFP Modules
<b>Cables:</b>	10/100Base: Cat5 or higher (100 meters max.) 1000Base: Cat5e or higher (100 meters max.) 1000Base-FX: Multi-Mode or Single-Mode Fiber Optic Cable
<b>Buffer Memory:</b>	112Kb
<b>MAC Addresses:</b>	Table with 8K entries
<b>VLAN:</b>	Port-based VLAN, 802.1Q Tag-based VLAN
<b>QoS:</b>	(4) Priority Queues, Classification: Port-based, 802.1p, IP DSCP
<b>Port Link Aggregation:</b>	Trunking Groups: 2 max., Ports/Group: 2
<b>LED Indication:</b>	Power Status TX Ports: Speed/Link/Act Status FX Port: Speed/Link/Act Status, Optical Link Status
<b>DC Power Input:</b>	Rating: +7.5VDC, 1A Consumption: 3.6Wmax. @ 7.5V
<b>Dimensions:</b>	5.67 x 4.11 x 1.02 inches (WxDxH)
<b>Environment:</b>	Operating Temperature: -0° C ~ +40° C Storage Temperature: -20° C ~ +70° C Relative Humidity: 10% to 90% non-condensing