

# 6-Port 10/100/1000 Ethernet Switch with (2) 1000Base SFP Slots

SG70660

## Technical Specifications

|                             |   |
|-----------------------------|---|
| <b>Standards:</b>           | 802.3u, 802.3z, 802.3ab   |
| <b>MAC Address Table:</b>   | 1K  |
| <b>Frame Buffer Memory:</b> | 1Mb   |
| <b>Switching Capacity:</b>  | 12Gbps  |
| <b>Connectors:</b>          | Copper Port: RJ-45<br>Fiber Ports: SFP Modules with LC Connectors   |
| <b>Cables:</b>              | Copper Port: Cat5 or Higher<br>Fiber Ports: Multi-Mode: 50/125 or 62.5/125<br>Single-Mode: 8/125 or 9/125         |
| <b>Flow Control:</b>        | Full Duplex: 802.3x Flow Control<br>Half Duplex: Back Pressure Flow Control                                       |
| <b>LED Indicators:</b>      | Power<br>Copper Port: Link/Activity, Speed<br>Fiber Ports: Link/Activity  |
| <b>Power Requirements:</b>  | Power Supply Input: 100-240VAC, 50~60Hz<br>Power Supply Output: 5VDC, 2A  |
| <b>Environment:</b>         | Operating Temperature: 0° C ~ +50° C<br>Storage Temperature: -20° C ~ +70° C<br>Humidity: 5% ~ 90% non-condensing |
| <b>Dimensions:</b>          | 5.51 x 3.94 x 1.18 inches (L x W x H)<br>140 x 100 x 30 mm (L x W x H)  |