

VersiVision - Fiber Optic Video

FVTM200xA - Transmitter
FVRM200xA - Receiver



Product Features

- 8-Bit Uncompressed Video Transmission
- NTSC, PAL or SECAM Video Compatible
- Transmit up to 30km without Optical Attenuation
- WDM Technology for Higher Reliability
- No EMI, RFI, Cross Talk or Video Distortion
- No Electrical or Optical Adjustments Required
- LED Indicators for Instant System Monitoring
- Stand-Alone or Rack-Mount in FVC18 Chassis
- Hot-Pluggable into the FVC18 Chassis



Product Description

The VERSITRON **VersiVision** Series video transmitters and receivers support 2-channels of 8-bit digitally encoded broadcast quality video over one multi-mode or single-mode optical fiber. The devices are directly compatible with NTSC, PAL, and SECAM camera systems. Plug and Play design ensures adjustment-free installation and operation, and optical adjustments are never required. LED indicators are provided to instantly monitor the system operating status. A typical installation utilizes a *transmitter* unit at the camera end of the link, connected via a single fiber optic cable, to a *receiver* unit at the monitoring end of the link. Devices are available for either stand-alone or rack-mount installation with the FVC18 18-Slot Chassis.

Product Models

Model	Function	Connector	Fiber Cable	Wavelength	Max Distance
FVTM2003A	Transmitter	ST Simplex	MM	1310nm	3 Km
FVRM2003A	Receiver	ST Simplex	MM	1310nm	3 Km
FVTM2005A	Transmitter	ST Simplex	SM	1310nm	30 Km
FVRM2005A	Receiver	ST Simplex	SM	1310nm	30 Km

ST-SC adapters are available for applications using SC fiber connectors.

VersiVision - Fiber Optic Video

FVTM200xA - Transmitter
FVRM200xA - Receiver



Technical Specifications

VIDEO

Video Input:	2 Volt pk-pk (75 Ohms)
Input/Output Channels:	2
Bandwidth:	5 Hz - 8 MHz
Bit Resolution:	8 - Bit
Differential Gain:	< ±1%
Differential Phase:	< ±1°
Tilt:	< 1%
S/N Ratio:	60dB (Weighted)

WAVELENGTH

Multi-Mode:	1310nm
Single-Mode:	1310nm

OPTICAL EMITTER

Laser Diode

Number of Fibers: 1

CONNECTORS

Optical:	ST
Video:	BNC

GENERAL

Power Supply:	5VDC, 2A
Dimensions:	4.33 x 4.09 x 1.10 Inches
MTBF:	> 100,000 Hours
Operating Temperature:	-35° C to +65° C
Storage Temperature:	-45° C to +85° C
Relative Humidity:	0% to 95% (non-condensing)



VersiVision - Fiber Optic Video

FVTM200xA - Transmitter
FVRM200xA - Receiver



Wiring Diagram

