

# SCOOOL

JUNIOR BIKES



12"

16"

18"

JUNIOR BIKES 12" - 18"


BEDIENUNGSANLEITUNG // MANUAL



[www.scool.de](http://www.scool.de)

**Legende**

- |   |   |
|---|---|
| 01 <b>Hinterreifen /</b> Rear tyre                            | 09 <b>Pedale /</b> Pedal  |
| 02 <b>Sattel mit Sattelstütze /</b> Saddle with seat post     | 10 <b>Kurbel / Kettenradgarnitur /</b> Crank / Chain wheel assembly |
| 03 <b>Rahmen /</b> Frame                                      | 11 <b>Kette /</b> Chain   |
| 04 <b>Lenker /</b> Handlebar                                  | 12 <b>Hinterradfelge /</b> Rear wheel rim                           |
| 05 <b>Brems- / Schalthebel /</b> Brake- / gear lever          | 13 <b>Schutzblech /</b> Mud Guard                                   |
| 06 <b>Vorderrad-Felgenbremse /</b> Front wheel calliper brake | 14 <b>Ventil /</b> Valve  |
| 07 <b>Vorderreifen /</b> Front tyre                           | 15 <b>Gabel /</b> Fork  |
| 08 <b>Vorderradfelge /</b> Front wheel rim                    |   |



Beispiel Abbildung

**Einleitung**

Herzlichen Glückwunsch zum Kauf Ihres neuen S'COOL Juniorbikes. Vielen Dank, dass Sie sich für ein Fahrrad unserer Marke entschieden haben. Damit verbinden Sie Qualität, Sicherheit und modernes Design. Bitte lesen Sie die Bedienungs- und Montageanleitung sorgfältig durch, sie enthält wichtige Informationen für den sicheren Betrieb sowie für die Wartung Ihres S'COOL Juniorbikes. Bei Fragen oder Problemen, wenden Sie sich bitte an Ihren Fachhändler.

**Verantwortung der Eltern**

Bei bestimmungsgemäßem Einsatz sind Gefährdungen während der Nutzung weitgehend ausgeschlossen. Bedenken Sie, dass durch das natürliche Bewegungsbedürfnis von Kindern und Jugendlichen, unvorhersehbare Situationen und Gefahren auftreten können, die eine Verant-

wortung seitens des Herstellers

ausschließen. Erklären Sie Ihrem Kind den korrekten Umgang mit dem S'COOL Juniorbike. Machen Sie Ihr Kind auf mögliche Gefahren aufmerksam.



**Warnhinweis**

Achten Sie darauf, dass Ihr Kind bei Benutzung dieses Juniorbikes geeignete Kleidung und Schuhe trägt. Schützen Sie Ihr Kind durch das Tragen eines Fahrradhelms. Lassen Sie Ihr Kind nur an sicheren Orten fahren. Sichern Sie Treppen, Gartenteiche, Schwimmbecken, sowie abschüssige Wege.

**Gebrauch**

Das Juniorbike bitte nur im geeigneten Bereich und außerhalb des öffentlichen Straßenverkehrs gebrauchen. Da es nicht der StVO entspricht, darf es nicht im Straßenverkehr eingesetzt werden. Das Kinderfahrrad entspricht der ISO 8098 bzw. ISO 4210 und die zulässige Gesamtbelastung beträgt max. 50 kg. Die Fahrbereitschaft ist unter Berücksichtigung der Körpergröße herzustellen. Der Sattel ist so einzustellen, dass die Fußsohlen des Kindes den Boden auch dann erreichen, wenn die Beine beim Fahren leicht angewinkelt werden. Den Lenker (inkl. Bremse und Glocke) bei eingestellter Sattelposition für das Kind leicht erreichbar einstellen.

Stützräder nur bei Bedarf als Lernhilfe am Hinterbau fest montieren. Die Nutzung der Stützräder ist nur im Rahmen einer kurzen Lernperiode zulässig, da sich langfristig und bei zunehmender Fahrpraxis, unkontrollierbare Kräfte auf den Rahmen auswirken.

Aus Fahrsicherheitsgründen wird empfohlen den Gepäckträger nicht als Lastenträger zu nutzen



**Achtung!**

Beachten Sie die ausreichende Mindesteinstecktiefe bei Lenker und Sattelstütze.

**Wartung und Pflege**

Achten Sie besonders auf die Verdrehfestigkeit des Lenkers und des Sattels! Kontrollieren Sie regelmäßig den Luftdruck. Beschädigte oder verformte Bauteile unbedingt austauschen. Originalersatzteile beziehen Sie über Ihren Fachhändler oder direkt über uns (coolmobility GmbH, Bielefeld).

- Beachten Sie die verminderte Bremswirkung der Vorderbremse bei Nässe.
- Plötzliches starkes Bremsen mit der Felgenbremse sollte vermieden werden, da sich das Fahrverhalten des Fahrrads dadurch verändern kann und zum Sturz führt.
- Bei langen Strecken sind Dauerbremsungen mit der Rücktrittsbremse zu vermeiden. Es kann zur starken Erwärmung der Rücktrittsnabe führen.
- Lässt sich der Handbremshebel um mehr als die Hälfte seines Weges an den Lenker heranziehen, muss die Bremse nachgestellt werden.
- Die Bremsfläche muss sauber und fettfrei sein. Die Bremsbelege müssen parallel zu einander stehen. Sie sollten in einem Abstand von 1mm unter der Felgenoberkante anliegen und leicht schräg zur Felge montiert werden.

- Abgefahrene Belege sind sofort auszutauschen. Achten Sie darauf Original-Beläge zu verwenden.
- Überprüfen Sie die Kettenspannung und stellen Sie sie ggfs. nach. Führen Sie Reparatur-, Wartungs- und Einstellarbeiten nur dann selber durch, wenn Sie über ausreichendes Fachwissen und entsprechendes Werkzeug verfügen. Insbesondere bei Arbeiten an der Bremsanlage. Ansonsten wenden Sie sich bitte an Ihren Fachhändler.



**Achtung!**

Ventilkappen sind fest anzuziehen und von Kindern fern zu halten (Verschluckungsgefahr). Nachträgliche Anbauten und Veränderungen an dem Fahrrad, verändern die Fahreigenschaften und können zu Gefahren führen.

**Verschleißteile:** Bereifung (inkl. Schläuche), Griffe, Bremse.  
Sauberkeit ist Korrosionsschutz (Rostschutz).

Verwenden Sie nur umweltfreundliche, keinesfalls aggressive Reinigungsmittel. Schützen Sie das Fahrzeug vor Streusalz und vermeiden Sie eine längere Lagerung in feuchten Räumen.

**Sachmängelhaftung**

Es gilt die gesetzliche Sachmängelhaftung. Schäden, die durch unsachgemäße Beanspruchung, Gewalteinwirkung, ungenügende Wartung oder durch Abnutzung entstehen, sind von der Sachmängelhaftung ausgeschlossen.

**ÜBERGABEPROTOKOLL**

**Fahrradtyp/Modell:**

---

**Rahmennummer:**

---

**Rahmenfarbe:**

---

**Laufgradgröße:**

---

**ggf. Federgabeltyp:**

---

**Anzahl der Gänge:**

---

**Besondere Merkmale/Kennzeichen:**

---

**Übergabe-Zustand:**

---

**Name und Anschrift des Eigentümers:**

---

**Kaufdatum:**

---

**gekauft bei:**


---

**(Firmenstempel)**

---

## Key

01	<b>Hinterreifen /</b> Rear tyre	09	<b>Pedale /</b> Pedal
02	<b>Sattel mit Sattelstütze /</b> Saddle with seat post	10	<b>Kurbel / Kettenradgarnitur /</b> Crank / Chain wheel assembly
03	<b>Rahmen /</b> Frame	11	<b>Kette /</b> Chain
04	<b>Lenker /</b> Handlebar	12	<b>Hinterradfelge /</b> Rear wheel rim
05	<b>Brems- / Schalthebel /</b> Brake- / gear lever	13	<b>Schutzblech /</b> Mud Guard
06	<b>Vorderrad-Felgenbremse /</b> Front wheel calliper brake	14	<b>Ventil /</b> Valve
07	<b>Vorderreifen /</b> Front tyre	15	<b>Gabel /</b> Fork
08	<b>Vorderradfelge /</b> Front wheel rim		



Example illustration

## Introduction

Congratulations on buying your new S'COOL Junior Bike. Thank you for choosing one of our bikes. They are known for their quality, safety and modern design. Please read through the user and assembly manual carefully: it contains important information for the safe use and proper maintenance of your S'COOL Junior Bike. If you have any questions or encounter a problem, please contact your dealer.

## Parental responsibility

When used as intended, there are few risks involved in using the bike. You should bear in mind that children and teenagers are naturally very active, and as a result unforeseeable situations and hazards may occur for which the manufacturer cannot be held liable. You should explain to your child the correct way of using the S'COOL Junior Bike. Make sure your child is aware of

potential hazards.



### Warning

Make sure your child wears suitable clothing and shoes when using the Junior Bike. Make sure your child is protected by wearing a cycling helmet. Only allow your child to ride in safe places. Close off steps and stairs, garden ponds, swimming pools and paths with steep downhill gradients.

### Use

Only use the Junior Bike in a suitable area and away from public highways. Given that it does not meet German Road Traffic Regulations (StVO), it must not be used on public highways. The bike conforms to the ISO 8098 resp. ISO 4210 standard and the maximum permitted load is 50 kg. The bike should be set up to suit the height of the user. The saddle should be adjusted so that your child can still reach the ground with the soles of their feet with legs slightly bent while riding. Once the saddle position has been adjusted, set the handlebars (including brake and bell) so that your child can easily reach them.

Only fit stabilisers to the rear end if they are needed to help your child learn to balance. The stabilisers should only be used as part of a brief learning period. This is because, over time and as your child becomes more experienced, the stabilisers will exert uncontrollable forces on the frame. For reasons of rider safety, we recommend not using the luggage rack as a load carrier.



### Caution!

Do not exceed the minimum insertion depth for handlebars and seat post – it provides a perfectly adequate lowest setting.

## Care and maintenance

Make particularly sure that the handlebars and saddle are properly secured and will not twist out of position. Check tyre pressure at regular intervals. Always replace damaged or miss-hapen components. You can order original spare parts via your dealer or directly from us (coolmobility GmbH, Bielefeld).

- Beware of the reduction in braking effect of the front brake in wet conditions.
- Sudden, sharp braking with the calliper brake should be avoided, as this can have a sudden impact on the bike's handling qualities, leading to the rider falling off.
- On long stretches, long periods of braking using the coaster brake should be avoided. This may lead to the coaster brake hub overheating.
- If the hand-operated brake lever can be pulled more than halfway towards the handlebars, the brake needs readjusting.
- The brake contact surfaces must be clean and free of grease. The brake pads must be parallel to one another. They should be at a distance of 1 mm below the top edge of the rim, fitted at a slight angle to the rim.
- Worn pads must be replaced immediately. Make sure that you use original pads.

- Check the chain tension and readjust it where necessary. Only carry out repair, maintenance and adjustment work yourself if you have adequate specialist knowledge and the right tools. This is particularly true of work on the brake system. Otherwise, please contact your dealer.



**Caution!**

Valve caps must be tightened securely and kept away from children. (Risk of swallowing) The making of later additions and modifications to the bike will alter the way it handles and is potentially dangerous.

**Wearing parts:** Tyres (including inner tubes), levers, brake. Cleanliness protects against corrosion (rust protection).

Only use environmentally friendly cleaning agents, never aggressive ones. Protect the bicycle from road salt and avoid storing it for long periods in damp areas.

**Warranty against defects**

The statutory warranty covering defects applies. Damage resulting from improper use, use of force, lack of maintenance, or wear and tear is excluded from the statutory defect warranty.

**HANDOVER PROTOCOL**

**Bicycle type/model:**

---

**Frame number:**

---

**Frame colour:**

---

**Wheel size:**

---

**Type of suspension fork, where appropriate:**

---

**Number of gears:**

---

**Specific features/distinguishing marks:**

---

**State in which handed over:**

---

**Name and address of owner:**

---

**Date of purchase:**

---

**Purchased from:**

---

**(Company stamp)**

---







coolmobility GmbH • Ludwig-Erhard-Allee 3 • 33719 Bielefeld

Tel. +49.521.32 99 88 - 0 • Fax +49.521.32 99 88 - 22

info@coolmobility.de • www.scool.de