

# Energy-related Datasheet

Regulation (EU) 2019/1782

<b>Manufacturer's name and address</b>	Shenzhen Baseus Technology Co., Ltd. 2 <sup>nd</sup> Floor, Building B, Baseus Intelligence Park, No.2008, Xuegang Rd, Gangtou Community, Bantian Street, Longgang District, Shenzhen
<b>Model identifier</b>	CCGAN40CE-M
<b>Input</b>	110-240V~, 50/60Hz, 1.5A Max.
<b>Output</b>	Type-C1 Output: 5.0V= 3.0A(15.0W); 9.0V= 3.0A(27.0W); 12.0V= 3.0A(36.0W); 15.0V= 2.67A(40.0W); 20.0V= 2.0A(40.0W) Max. Type-C2 Output: 5.0V= 3.0A(15.0W) 9.0V= 3.0A(27.0W); 12.0V= 3.0A(36.0W) 15.0V= 2.67A(40.0W); 20.0V= 2.0A(40.0W) Max. Total Output: 20.0W+20.0W Max. 20.0W: 5.0V= 3.0A(15.0W); 9.0V= 2.22A(20.0W); 12.0V= 1.5A(18.0W) Max.
<b>Average active efficiency</b>	82.00%
<b>Efficiency at low load(10%)</b>	62.63%
<b>No-load power consumption</b>	0.073W