

Energy-related Datasheet

Regulation (EU) 2019/1782

Manufacturer's name and address	Shenzhen Baseus Technology Co., Ltd. 2 nd Floor, Building B, Baseus Intelligence Park, No.2008, Xuegang Rd, Gangtou Community, Bantian Street, Longgang District, Shenzhen
Model identifier	CCXFK65CE
Input	110-240V~, 50/60Hz, 1.5A Max.
Output	Type-C1/Type-C2 Output: 5.0V= 3.0A (15.0W); 9.0V= 3.0A (27.0W); 12.0V= 3.0A (36.0W); 15.0V= 3.0A (45.0W); 20.0V= 3.25A (65.0W) Max. USB Output: 5.0V= 3.0A (15.0W); 9.0V= 3.0A (27.0W); 12.0V= 2.5A (30.0W); 20.0V= 1.5A(30.0W) Max. Type-C1+Type-C2 Output: 45.0W+20.0W Max. Type-C1+USB Output: 45.0W+18.0W Max. Type-C2+USB Output: 5.0V= 3.0A, 15.0W Max. Type-C1+(Type-C2+USB) Total output: 45.0W+15.0W Max. 45.0W: 5.0V= 3.0A (15.0W); 9.0V= 3.0A (27.0W); 12.0V= 3.0A (36.0W); 15.0V= 2.5A (37.5W); 20.0V= 2.25A (45.0W) Max. 20.0W: 5.0V= 3.0A (15.0W); 9.0V= 2.22A (20.0W); 12.0V= 1.67A (20.0W) Max. 18.0W: 5.0V= 3.0A (15.0W); 9.0V= 2.0A (18.0W); 12.0V= 1.5A (18.0W) Max.
Average active efficiency	81.88%
Efficiency at low load(10%)	62.45%
No-load power consumption	0.187W