

USAGE:

·ROAD-COOL engine coolant is a pre-mixed ready for use product and requires no further dilution.

ROAD-COOL coolant can be added to most conventional coolants. However, to get maximum performance and protection it is recommended to drain and flush the radiator before filling with ROAD-COOL.

STORAGE AND HANDLING:

·ROAD-COOL engine coolant should be stored above –20°C and preferably at ambient temperatures. Periods of exposure to temperatures above 35°C should be minimised.

TOXICITY AND SAFETY:

•Warning: ROAD-COOL contains ethylene glycol, which is harmful or fatal if swallowed. Avoid eye or skin contact. If swallowed, do NOT induce vomiting, contact a doctor at once. If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If in eyes, hold eyelids apart and flush the eye continuously with running water for at least 15 minutes. Seek medical attention if irritation persists.

For advice, contact a Poisons Information Centre (Australia 13 11 26 / NZ 0800 764 766).

·Further ENVIRONMENT, HEALTH and SAFETY Information is available on this product in the Safety Data Sheet (SDS). Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal.

·To obtain the SDS or MDS for this product, please contact us sales@abindustries.co.nz