



Quick Start-Up Tips

FROGPRODUCTS.COM | 800.222.0169

Download the **FREE**
FROG Water Care® App



1

If previously using bromine or biguanides, drain, rinse and refill the hot tub. Otherwise proceed to Step 2.

2

Test the water with FROG® @ease® Test Strips and balance according to the Water Balance Guidelines.

Water Balance Guidelines

Total Alkalinity..... 80 - 120 ppm
pH..... 7.2 - 7.8
Total Hardness..... 150 - 250 ppm

PLUS, a convenient
Out Indicator reading
for SmartChlor®.



3

Shock the hot tub with FROG® Jump Start® to achieve a start-up level of chlorine.



4

Connect the blue FROG @ease Mineral Cartridge to the silver FROG @ease SmartChlor Cartridge and twist to lock.

TOP HALF
FROG @ease
Mineral Cartridge




BOTTOM HALF
FROG @ease
SmartChlor Cartridge



5

Set the dial on the bottom of the FROG @ease SmartChlor Cartridge per the setting chart.

Setting # on the FROG @ease
SmartChlor Cartridge



SmartChlor Cartridge Settings

Gallons	Setting #
200-299	1
300-450	2
451-550	3
551-600	4

6

Place in the hot tub and enjoy weeks of Fresh Mineral Water® hot tub care.



7

Test weekly with FROG @ease Test Strips. When the FROG @ease system flips over, replace the silver SmartChlor Cartridge. The Cartridge lasts 3-4 weeks depending on hot tub size and usage.



Reduces chlorine
use up to 75%*

Please recycle
SmartChlor Cartridge,
if possible.



8

Shock the hot tub with FROG Maintain® once a month, or when replacing your SmartChlor Cartridge.



*For pools and hot tubs. *Compared to the minimum ANSI recommended chlorine level of 2.0 ppm for a hot tub.
©2022 King Technology Inc.