

1000BASE 1310nm-TX/1550nm-RX U 60Km LC



Popular Compatibility Options

Vendor	Part Code
Wire	1000BASE-BX-60U15-WR
Cisco	GLC-BX60-U-WR
Juniper	SFP-GE60KT13R15-WR
Arista	1000BASE-BX-60U-A-WR
HPe	SFP-1G-BXD-60-WR
H3C	SFP-GE-LH60-SM15500-WR
Brocade	E1MG-1G-BXU-60-WR

75+ other vendors available

>1000BASE-1310nm-TX/1550nm-RX 60Km Specifications

Form Factor:	SFP
Data Rate:	1Gbps
Tx/Rx:	1310nmTX/1550nmRX
Compatible with:	See table
Reach:	60Km
Cable Type:	SMF
DDM/DOM:	Yes
Connector Type:	Duplex-LC
TX Power:	0 to -5dBm
Minimum Receiver Sens:	-26dBm
Power Budget:	19dBm
Temperature Range:	0-70°C
Warranty:	Lifetime

>Features

- Hot pluggable
- Protocol- Fast Ethernet, Gigabit Fibre Channel, MSA Compliant
- RoHS-6 compliant
- Built-in digital diagnostic function
- Compliant with OEM vendor multi-source agreement

>Testing

- Compatibility Tested
- Performance Tested
- 100% Testing of all Transceiver

>Description

This 1000BASE-1310nm-Tx/1550nm-RX 60Km SFP transceiver provides 1G throughput up to 60Km over Single-Mode Fibre (SMF) using a wavelength of 1310nm - 1550nm via an LC connector. It is guaranteed to be 100% compatible with the host device.

Digital Optical Monitoring (DOM) support is also present to allow access to real-time operating parameters. We stand behind the quality of our products and proudly offer a lifetime warranty.