

# 100G QSFP28 to QSFP28 Passive DAC



## Popular Compatibility Options

Vendor	Part Code
Wire	100G-DAC-xM-WR
Cisco	QSFP-100G-CUxM-WR
Juniper	EX-QSFP-100GE-DAC-xM
Juniper	QFX-QSFP-100GE-DAC-xM
Juniper	JNP-QSFP-100GE-DAC-xM
Arista	CAB-Q-Q-100G-xM-WR
Brocade	100G-Q28-Q28-C-x-WR
Dell	470-ABPWWR
HPe Aruba	

75+ other vendors available

### >100G QSFP28 to QSFP28 DAC Spec

Form Factor:	QSFP28
Data Rate:	100Gbs
Compatible with:	See table
Wire AWG:	30AWG
Interface Type:	QSFP28 to QSFP28
DDM/DOM:	Yes
Minimum Bend Radius:	46mm
Power Supply:	3.3V
Temperature Range:	0-70°C
Jacket Material:	LSZH
Warranty:	Lifetime - See Warranty Document

### >100G QSFP28 to QSFP28 DAC Feature

- Supports upto 100 Gb/s bit rates
- Built-in Digital Diagnostic Function
- Passive Copper Twinax Cable
- RoHs-6 compliant
- Built-in digital diagnostic function
- Compliant with OEM vendor multi-source agreement

### >Testing

- Compatibility Tested
- Performance Tested
- 100% Testing of all Transceiver

### >Description

This is a multi-vendor compatible 100GBase-CU QSFP28 to QSFP28 Direct attach cable that operates over passive copper with a maximum reach of 5.0m. It has been programmed, uniquely serialized, data-traffic and application tested to ensure it is 100% compliant and functional. It is guaranteed to be compatible with the OEM host switch, router or network interface card (NIC). This Direct Attach Cable is built to comply with MSA (Multi-Source Agreement) standard. Digital Optical Monitoring (DOM) support is also present to allow access to real-time operating parameters. We stand behind the quality of our products and proudly offer a lifetime warranty.