


25GBASE-ESR SFP28 850nm 300m



Popular Compatibility Options

| Vendor | Part Code |
|---------|--------------------|
| Wire | 25GBASE-ESR-WR |
| Cisco | SFP-25G-ESR-S-WR |
| Juniper | EX-SFP-25G-ESR-WR |
| Juniper | QFX-SFP-25G-ESR-WR |
| Juniper | JNP-SFP-25G-ESR-WR |
| Brocade | 25G-SFP28-ESR-WR |
| Arista | SFP-25G-ESR-AR-WR |

75+ other vendors available

>25GBASE - ESR Specifications

| | |
|----------------------|----------------------------------|
| Form Factor: | SFP28 |
| Data Rate: | 25.78Gbs |
| Tx/Rx Wavelength: | 850nm |
| Compatible with: | See table |
| Reach: | 300m |
| Cable Type: | MMF |
| DDM/DOM: | Yes |
| Connector Type: | Duplex-LC |
| Tx Power | -6.4~2.4dBm |
| Receiver Sensitivity | <-10.3dBm |
| Power budget | 3.9dB |
| Temperature Range: | 0-70°C |
| Warranty: | Lifetime - See Warranty Document |

>25GBASE - ESR Features

- Hot pluggable
- Protocol- SFF-8472 IEEE 802.3AH-2004
- RoHs-6 compliant
- Built-in digital diagnostic function
- Compliant with OEM vendor multi-source agreement

>Testing

- Compatibility Tested
- Performance Tested
- 100% Testing of all Transceiver

>Description

This 25GBASE compatible SFP28 transceiver provides 25Gbps throughput up to 300m over Multimode Fibre (MMF) using a wavelength of 850nm via an LC connector. It is guaranteed to be 100% compatible with the host device.

Digital Optical Monitoring (DOM) support is also present to allow access to real-time operating parameters. We stand behind the quality of our products and proudly offer a lifetime warranty.