

25GBASE-SR SFP28 850nm 100m



Popular Compatibility Options

Vendor	Part Code
Wire	25GBASE-SR-WR
Cisco	SFP-25G-SR-S-WR
Juniper	EX-SFP-25G-SR-WR
Juniper	QFX-SFP-25G-SR-WR
Juniper	JNP-SFP-25G-SR-WR
Mellanox	MMA2P00-AS-WR
Brocade	25G-SFP28-SR-WR
HPe	JL484A-WR
Dell	407-BBWK-WR
Extreme	10GB-SR-SFPP-WR
Arista	SFP-25G-SR-WR

75+ other vendors available

>25GBASE - SR Specifications

Form Factor:	SFP28
Data Rate:	25.78Gbs
Tx/Rx Wavelength:	850nm
Compatible with:	See table
Reach:	100m
Cable Type:	MMF
DDM/DOM:	Yes
Connector Type:	Duplex-LC
Tx Power	-8~3dBm
Receiver Sensitivity	<-11dBm
Power budget	3dB
Temperature Range:	0-70°C
Warranty:	Lifetime - See Warranty Document

>25GBASE - SR Features

- Hot pluggable
- Protocol- SFF-8472 IEEE 802.3AH-2004
- RoHS-6 compliant
- Built-in digital diagnostic function
- Compliant with OEM vendor multi-source agreement

>Testing

- Compatibility Tested
- Performance Tested
- 100% Testing of all Transceiver

>Description

This 25GBASE compatible SFP28 transceiver provides 25Gbps throughput up to 100m over Multimode Fibre (MMF) using a wavelength of 850nm via an LC connector. It is guaranteed to be 100% compatible with the host device.

Digital Optical Monitoring (DOM) support is also present to allow access to real-time operating parameters. We stand behind the quality of our products and proudly offer a lifetime warranty.