

25GBASE SFP28 DAC



Popular Compatibility Options

Vendor	Part Code
Wire	25G-DAC-XM-WR
Cisco	SFP-H25GB-CU-XM-WR
Juniper	JNP-25G-DAC-XM-WR
Arista	CAB-S-S-25G-XM-WR
Extreme	1052X-WR

75+ other vendors available

>25G DAC Specifications

Connector A:	SFP28
Connector B:	SFP28
Data Rate:	25Gbs
Compatible with:	See table
Available Lengths:	0.5m, 1m, 1.5m, 2m, 2.5m, 3m, 4m, 5m
Cable Material:	LSZH
Minimum Bend Radius:	23mm
Power Supply:	3.3v
Power Consumption:	≤0.1W
Temperature Range:	0-70°C
Warranty:	Lifetime - See Warranty Document

>25G DAC Features

- Hot pluggable
- Protocol- SFF-8431, IEEE 802.3ae
- RoHs-6 compliant
- Compliant with OEM vendor multi-source agreement

>Testing

- Compatibility Tested
- Performance Tested
- 100% Testing of all Transceiver

>Description

This 25GBase compatible SFP28 to SFP28 direct attach cable operates over passive copper with a maximum reach of 5.0m. It has been programmed and application tested to ensure it is 100% compliant and functional. This direct attach cable is TAA (Trade Agreements Act) compliant, and is built to comply with MSA (Multi-Source Agreement) standards. We stand behind the quality of our products and proudly offer a limited lifetime warranty.