

40G QSFP+ to QSFP+ Passive DAC



Popular Compatibility Options

Vendor	Part Code
Wire	40G-DAC-xM-WR
Cisco	QSFP-H40G-CUxM
Juniper	EX-QSFP-40GE-DAC-xM
Juniper	QFX-QSFP-DAC-xM
Juniper	JNP-QSFP-DAC-xM
Arista	CAB-Q-Q-xM
Brocade	40G-QSFP-C-0x01
Dell	CBL-QSFP-40GE-xM
HPe Aruba	R9G01A

75+ other vendors available

>40G QSFP+ to QSFP+ DAC Spec

Form Factor:	QSFP+
Data Rate:	40Gbs
Compatible with:	See table
Wire AWG:	30AWG
Interface Type:	QSFP+ to QSFP+
DDM/DOM:	Yes
Minimum Bend Radius:	23mm
Power Supply:	3.3V
Temperature Range:	0-70°C
Jacket Material:	LSZH
Warranty:	Lifetime - See Warranty Document

>40G QSFP+ to QSFP+ DAC Feature

- Supports 39.994 to 41.5 Gb/s bit rates
- Built-in Digital Diagnostic Function
- Passive Copper Twinax Cable
- RoHS-6 compliant
- Built-in digital diagnostic function
- Compliant with OEM vendor multi-source agreement

>Testing

- Compatibility Tested
- Performance Tested
- 100% Testing of all Transceiver

>Description

This is a multi-vendor compatible 40GBase-CU QSFP+ to QSFP+ Direct attach cable that operates over passive copper with a maximum reach of 5.0m. It has been programmed, uniquely serialized, data-traffic and application tested to ensure it is 100% compliant and functional. It is guaranteed to be compatible with the OEM host switch, router or network interface card (NIC). This Direct Attach Cable is built to comply with MSA (Multi-Source Agreement) standard. Digital Optical Monitoring (DOM) support is also present to allow access to real-time operating parameters. We stand behind the quality of our products and proudly offer a lifetime warranty.