


40GBASE-LRL4

QSFP+ 1310nm 2km



Popular Compatibility Options

| Vendor | Part Code |
|----------|----------------------|
| Wire | 40GBASE-LRL4-WR |
| Cisco | QSFP-40GE-LRL4-WR |
| Juniper | JNP-QSFP-40GE-IR4-WR |
| Juniper | QSFP-40GBASE-LR4 |
| Juniper | EX-QSFP-40GE-IR4-WR |
| Mellanox | MC2210511-IR4-WR |
| HPe | JL286A-WR |
| Arista | QSFP-40G-LRL4-AR-WR |

75+ other vendors available

>40GBASE-LRL4 Specifications

| | |
|-----------------------|----------------------------------|
| Form Factor: | QSFP+ |
| Data Rate: | 41.25Gbs (4x 10.3Gbps) |
| Tx/Rx Wavelength: | 1310nm |
| Compatible with: | See table |
| Reach: | 2km |
| Cable Type: | SMF |
| DDM/DOM: | Yes |
| Connector Type: | Duplex-LC |
| TX Power: | -7~2.3dBm |
| Receiver Sensitivity: | <-11.5dBm |
| Power Budget: | 4.5dB |
| Temperature Range: | 0-70°C |
| Warranty: | Lifetime - See Warranty Document |

>40GBASE-LRL4 Features

- Hot pluggable
- Protocol- 40G Ethernet, Fibre Channel, SATA/SAS3, MSA Compliant
- RoHS-6 compliant
- Built-in digital diagnostic function
- Compliant with OEM vendor multi-source agreement

>Testing

- Compatibility Tested
- Performance Tested
- 100% Testing of all Transceiver

>Description

This 40GBase compatible QSFP+ transceiver provides 40G throughput up to 2km over Singlemode Fibre (SMF) using a wavelength of 1310nm via an LC connector. It is guaranteed to be 100% compatible with the host device.

Digital Optical Monitoring (DOM) support is also present to allow access to real-time operating parameters. We stand behind the quality of our products and proudly offer a lifetime warranty.