

# IEC C14-C15 LSZH/LSOH Power Cable



## Wire Product Codes

C14-C15-0.5M-WR  
C14-C15-1M-WR  
C14-C15-1.5M-WR  
C14-C15-2M-WR  
C14-C15-3M-WR

## Standards

**H05Z1Z1**- European LSZH Designation  
**IEC 60320** – International Standard 3.0  
**RoHs-6** – Free from Lead

Lifetime warranty – Quality Assured

## IEC C14-C15 Specifications

<b>Connector A:</b>	IEC 60320 C14
<b>Connector B:</b>	IEC 60320 C15
<b>Max Ampere:</b>	15A
<b>European Designation:</b>	H05Z1Z1-F
<b>Conductors Size:</b>	1.5mm <sup>2</sup>
<b>Number of Conductors:</b>	3
<b>Wire AWG:</b>	14 AWG
<b>Cable Outer Diameter:</b>	9.5 ± 0.2mm
<b>Jacket Temp. Rating:</b>	105°C
<b>Jacket Colour:</b>	Black
<b>Jacket Material:</b>	LSZH
<b>Warranty:</b>	Lifetime - See Warranty Document

## Description

This industry universal IEC C14 to C15 Power extension cable, operates with oxygen-free copper conductors for low resistance to increase conductivity and uphold a stable transmission. All our power cables have been power-traffic and application tested to ensure they are 100% compliant and functional. They are guaranteed to be compatible with all Power Distribution Units (PDU), Switches, Routers and POE Injectors.

We stand behind the quality of our products and proudly offer a lifetime warranty.

## IEC C14-C15 Features

- The C14 (male) is a plug whereas the C15 (female) is an outlet or socket of the same mating pair format.
- RoHs-6 compliant.
- Compliant with all the industries PDU's and IT equipment such as Switches, Routers and POE Injectors.

## Testing

All power cords have been vigorously tested to ensure they are low smoke zero halogen compliant.

## Available Lengths

**0.5m, 1m, 1.5m, 2m, 3m**