

IEC C20-C19 LSZH/LSOH Power Cable



Wire Product Codes

C20-C19-1M-WR
C20-C19-1.5M-WR
C20-C19-2M-WR
C20-C19-3M-WR
C20-C19-5M-WR

Standards

H05Z1Z1- European LSZH Designation
IEC 60320 – International Standard 3.0
RoHs-6 – Free from Lead

Lifetime warranty – Quality Assured

IEC C20-C19 Specifications

Connector A:	IEC 60320 C20
Connector B:	IEC 60320 C19
Max Ampere:	20A
European Designation:	H05Z1Z1-F
Conductors Size	1.5mm ²
Number of Conductors:	3
Wire AWG:	12 AWG
Cable Outer Diameter:	11 ± 0.3mm
Jacket Temp. Rating:	105°C
Jacket Colour:	Black
Jacket Material:	LSZH
Warranty:	Lifetime - See Warranty Document

Description

This industry universal IEC320 C20 to IEC320 C19 Power extension cable, operates with oxygen-free copper conductors for low resistance to increase conductivity and uphold a stable transmission. All our power cables have been power-traffic and application tested to ensure they are 100% compliant and functional. They are guaranteed to be compatible with all Power Distribution Units (PDU) and uninterruptible Power Supplies (UPS).

We stand behind the quality of our products and proudly offer a lifetime warranty.

IEC C20-C19 Features

- The C20 (male) is a plug whereas the C19 (female) is an outlet or socket of the same mating pair format.
- RoHs-6 compliant.
- Compliant with all the industries PDU's and UPS's Power Connections.
- Thick 12 AWG wire gauge manages high power levels required for larger equipment.

Testing

Each individual cord is performance and quality tested to ensure failure rate is below industry standard.

Available Lengths

1m, 1.5m, 2m, 3m, 5m