

SOLUTION 5 BIOETHANOL

Supplier name	Arada
Product Code	SOL5-BIO

Dimensions

Width (inc. Floor Fixings)	440 mm
Height (inc. Hot Plate)	558 mm
Depth (inc. Door Handle)	385 mm





Performance


Fuel Type	Bioethanol	
Burner capacity (Max inc. Overfill 1 Litre)	0.8 Litre	
Nominal Heat Output To Room	2.46 kW	
Max Burn Rate	0.35 L / Hr	
Typical Run Time (approximate)	2 to 4.5 Hrs	


Features

Stove body type	Freestanding
Body thickness	3mm Steel
Cast Iron door	Yes
Optional decorative flue compatibility	Fits standard 5inch flue collar and flue pipe
Suitable for non- combustible 12mm hearth	Yes
Nett Weight	40 Kg
Gross Weight	49 Kg









Minimum Distance to Surrounding Materials

Install location	Rear	Per Side	Тор	Notes
Alcove or recess	50 mm	75 mm	200 mm	Included limit screws must be fitted *
Freestanding	100 mm	200 mm	300 mm	Included limit screws not required *

Specific precautions to be taken when the local space heater is assembled, installed or maintained:

 $Product \ should \ be \ installed \ in \ accordance \ with \ local \ building \ regulations. \ Appliance \ will \ become \ very \ hot \ during \ use.$

An approved (BS-EN 50291) and working Carbon Monoxide (CO) alarm should be installed in the same room where the appliance is being fired.

Installation and operating instructions for this stove are available online at www.aradastoves.com/support

BK999 / SOL5-BIO 25/11/2024

^{*} For more information please refer to document (BK778) Bioethanol Stove User Guide section 3.4