

Dyness RV12100 is custom-made for outdoor travel. To meet your various requirements.









Model	RV12100
Battery Type	LiFePO4
Nominal Battery Energy	1.28kWh
Nominal Capacity	100Ah
Nominal Voltage	12.8V
Operating vol.Range	14.6V
Discharging End-of vol.	11.2-14.6V
Nominal Power Output	0.64kW
Recommended Charge/Discharge Current	50A
Peak Power Charge/Discharge Current	100A(15s)
Depth of Discharge	90%
Net Weight	30.861bs
Dimension [W*D*H, inch]	12*7.2*7.3
Charging Temp. Range	32°F~131°F
Discharging Temp. Range	-4°F~131°F
Communication	CAN/RS485
Warranty	5 Years
Warranty Document Supplied	Yes
Calendar Life	6000 Cycles
Enclosure Protection	NEMA1
Expansion	Up to 16 modules to parallel
Alarms	Overcharge/Overdischarge/Overcurrent/ Overtemperature/Short Circuit
Compatible Inverters	Victron, Must, Steca

[1]Test conditions:0.2C Charging/Discharging,@77 \mathbb{F} ,80% DOD

MOUI Native field	
RV12	V 12100 Am Ballery Moule DYNESS BALLEY OFFICIAL STREET 2 100