



## FRIGOL TZ-19

### GENERAL FEATURES:

FRIGOL Refrigeration Compressor Oils are obtained by refining oil fractions extracted through straight-run distillation of paraffin-free petroleum.

### APPLICATION:

They are intended for use in ammonia refrigeration compressors with evaporator temperatures of up to -30°C, e.g. uniflow compressors with oil recirculation systems.

### STANDARDS, APPROVALS. SPECIFICATION:

PN-74/C-96072

### PHYSICAL AND CHEMICAL PROPERTIES:

Parametry	Jedn.	Wartości typowe
Kinematic viscosity at 20°C	mm <sup>2</sup> /s	91,1
Kinematic viscosity at 40°C	mm <sup>2</sup> /s	33,2
Kinematic viscosity at 50°C	mm <sup>2</sup> /s	21,8
Kinematic viscosity at -30°C	mm <sup>2</sup> /s	-
Kinematic viscosity at -20°C	mm <sup>2</sup> /s	4380
Flash point	°C	212
Freezing point	°C	-37
Acid number	mg KOH/g	0,015
Ash content	%	0,004

Note: The above values of physical and chemical properties are typical values. Actual values are specified in quality certificates enclosed with each product lot.

### VERSION:

1 / 2023.07.17

