

TECHNICAL DATA SHEET

PROWAY 2

PREMIUM SLIDEWAY LUBRICANT

PROWAY 2 is a slideway lubricant that is compounded from premium virgin paraffinic base stocks and specially selected additives.

Applications

PROWAY 2 is recommended for the lubrication of planes, grinders, milling machines, shapers, boring machines, jig borers and other equipment involving slow-moving parts, extreme machining precision or heavily loaded way surfaces.

Recommendation for Use

PROWAY 2 is recommended as a way lubricant.

Benefits

- Excellent oxidation and thermal stability
- Resists formation of sludge and breakdown of oil in use to ensure maximum oil life

Health, Safety and Handling

Please consult the Safety Data Sheet (SDS) for information on storage, safe handling and disposal. The conditions or methods of handling, storage, use and disposal of the product are beyond our reasonable control – we assume no liability for any ineffectiveness of the product or any injury or damage, arising out of or in connection with these conditions.

Properties

PROPERTY	TYPICAL VALUE	UNIT
Viscosity at 40°C (ASTM D-445)	68	cSt
Specific Gravity at 60 °F (ASTM D-1298)	0.90	
Pour Point (ASTM D-97)	20	°F
Flash Point (C.O.C) (ASTM D-92)	430	°F

All reasonable care has been taken to ensure this publication is accurate upon issue. Such information may be affected by changes subsequent to issue. This Technical Data Sheet is to be used solely for this product. Prior to any use, consult the Safety Data Sheet (SDS) for information on hazard risks and product use parameters. All liability and all warranties express or implied are hereby excluded as to product performance results, the accuracy of these data including any warranty of merchantability or fitness for any purpose.

