TECHNICAL DATA SHEET

WOCO® HEP GEAR OIL 460

EXTREME PRESSURE GEAR OIL

WOCO® HEP GEAR OIL 460 is a premium quality extreme pressure gear lubricant formulated with high viscosity index base oils. This product contains a sulfur-phosphorus additive package. WOCO® HEP Gear Oil 460 possess good adhesion properties, are not-corrosive and are foam inhibited. The product resists oxidation, is thermally stable and has good demulsibility.

Applications

WOCO® HEP GEAR OIL 460 is recommended for circulating, splash, bath or spray lubrication systems on enclosed gear, chain or sprocket drives.

Recommendations for Use

Recommended as an extreme pressure gear oil

Health, Safety and Handling

Please consult the Safety Data Sheet (SDS) for information on storage, safe handling and disposal. The conditions or methods of handling, storage, use and disposal of the product are beyond our reasonable control - we assume no liability for any ineffectiveness of the product or any injury or damage, arising out of or in connection with these conditions.

WOCO® HEP GEAR OIL 460 is available in 5 gallon pails, 55 gallon drums, 275 gallon totes, or bulk delivery.

Benefits

- Excellent E.P. and load carrying capabilities
- Outstanding oxidation and thermal stability for longer service life
- Low foam tendency
- Excellent water separation
- Good adhesion properties
- General Motors GM LS2 Approval

Properties

PROPERTY	TYPICAL VALUE	UNIT
AGMA Grade	7	EP
Gravity	27	°API
Viscosity at 40°C at 100°C	460 30	cSt
Viscosity Index	95	
Flash Point (C.O.C)	540	۴F
Pour Point	-2	°C
Copper Strip Corrosion (ASTM D130)	1b	
Timken EP	60	lbs
Cleanliness, ISO	20/18/14	
FZG Pass Stage	12	

All reasonable care has been taken to ensure this publication is accurate upon issue. Such information may be affected by changes subsequent to issue. This Technical Data Sheet is to be used solely for this product. Prior to any use, consult the Safety Data Sheet (SDS) for information on hazard risks and product use parameters. All liability and all warranties express or implied are hereby excluded as to product performance results, the accuracy of these data including any warranty of merchantability or fitness for any purpose.

