

TECHNICAL DATA SHEET

WOCO® PREMIUM 100 PROCESS OIL

WOCO® PREMIUM 100 is based on a highly refined paraffinic distillate. Its high viscosity index allows it to be used in the formulation of many high quality lubricants such as motor oils, hydraulic oils, and a wide range of military oils.

Applications

WOCO® PREMIUM 100 can also be used as a metalworking lubricant in operations such as the grinding, de-burring, and light-duty machining of steels, brass and bronze. Premium 100 also serves as an excellent process oil in many rubber formulations.

Health, Safety and Handling

Please consult the Safety Data Sheet (SDS) for information on storage, safe handling and disposal. The conditions or methods of handling, storage, use and disposal of the product are beyond our reasonable control - we assume no liability for any ineffectiveness of the product or any injury or damage, arising out of or in connection with these conditions.

Benefits

- High viscosity index
- Can also be used as a metalworking lubricant

Properties

PROPERTY	TYPICAL VALUE	UNIT
Viscosity at 100°F	103	SUS
Flash Point	370	°F
Pour Point	+10	°F
API Gravity	2	
Water Content	30	ppm
Color Gardner	1	

All reasonable care has been taken to ensure this publication is accurate upon issue. Such information may be affected by changes subsequent to issue. This Technical Data Sheet is to be used solely for this product. Prior to any use, consult the Safety Data Sheet (SDS) for information on hazard risks and product use parameters. All liability and all warranties express or implied are hereby excluded as to product performance results, the accuracy of these data including any warranty of merchantability or fitness for any purpose.

