

10.375"



BIOESQUE®

# SMOKE & ODOR ENCAPSULANT

ADVANCED FORMULA · STAIN BLOCKING

CLEAR



ADVANCED STAIN BLOCKING FORMULA



FAST DRYING



LONG TERM PROTECTION

**SURFACE PREP:** SURFACES TO BE COATED MUST BE FREE OF DEBRIS, DUST, MILDEW, MOLD, DIRT, GREASE, LOOSE PAINT, OIL, GLUE, CALUMINE, WAX, SOAP AND OTHER SURFACE CONTAMINATION. PATCH IRREGULARITIES WITH VINYL PATCHING PASTE OR AN APPROPRIATE PATCHING COMPOUND. **APPLICATION:** APPLY GENEROUSLY AND UNIFORMLY BY BRUSH, ROLLER OR AIRLESS SPRAY EQUIPMENT AND ENSURE THAT THE FINISHED SURFACE IS PROPERLY SEALED. TWO COATS MAY BE REQUIRED ON SOME POROUS SURFACES. **DRYWALL:** JOINT CEMENT SHOULD BE SANDED SMOOTH BUT AVOID ABRADING THE PAPER. **STORAGE:** STORE IN A COOL, DRY ENVIRONMENT. KEEP CONTAINER CLOSED WHEN NOT IN USE. DO NOT MIX WITH STRONG ACIDS OR OXIDIZERS. DO NOT FREEZE. **READY TO USE.** STIR THOROUGHLY. DO NOT MIX WITH OTHER COATINGS, OR SOLVENTS. BIOESQUE IS SELF-PRIMING OVER BARE GYPSUM DRYWALL, COMPOSITION BOARD, CEILING TILE AND CONCRETE. DO NOT APPLY WHEN AIR OR SURFACE TEMPERATURE IS BELOW 50°F OR WHEN DRYING CONDITIONS ARE POOR. USE ADEQUATE VENTILATION DURING APPLICATION. **TINTING:** UP TO 2 OZ OF PIGMENT PER GALLON (WHITE ONLY). **THINNING:** IF THINNING IS REQUIRED, ADD A MAXIMUM OF 8 OZ OF WATER PER GALLON OF COATING. **APPLICATION:** APPLY BIOESQUE SMOKE & ODOR ENCAPSULANT GENEROUSLY AND UNIFORMLY BY BRUSH, ROLLER OR AIRLESS SPRAY EQUIPMENT AND ENSURE THAT THE FINISHED SURFACE IS PROPERLY SEALED. TWO COATS MAY BE REQUIRED ON SOME POROUS SURFACES. **BRUSH:** SYNTHETIC, NYLON OR POLYESTER BRISTLES. **ROLLER:** SYNTHETIC FIBER 3/8" NAP OR LONGER. **SPRAY:** .015 TO .019 TIP @ 2000-2800 PSI. **COVERAGES: SMOOTH SURFACES:** 350-600 FT<sup>2</sup>/GAL. **POROUS SURFACES:** 250-300 FT<sup>2</sup>/GAL. **DRY TIME:** BIOESQUE DRIES TO THE TOUCH IN 30 MINUTES AND CAN BE RECOATED IN 1 HOUR. FOR OPTIMAL PROTECTION, APPLY TOPCOAT WITHIN 72 HOURS OF APPLICATION. FULL ADHESION AND HARDNESS DEVELOPS IN 7 DAYS. **CLEAN-UP:** CLEAN ALL APPLICATION TOOLS WITH WARM SOAPY WATER. WIPE UP SPILLS IMMEDIATELY WITH A CLEAN DAMP CLOTH. FOLLOW EQUIPMENT MANUFACTURER'S DIRECTIONS TO CLEAN SPRAY EQUIPMENT. DISPOSE OF WASTE ACCORDING TO ALL EXISTING LOCAL, STATE AND FEDERAL REGULATIONS. **HVAC SYSTEMS: SURFACE PREPARATION:** ALWAYS FOLLOW INDUSTRY ACCEPTED CLEANING PROCEDURES BEFORE APPLICATION. ALL ACCUMULATED MOLD, DUST AND LOOSE PARTICLES NEED TO BE CLEANED AND REMOVED PRIOR TO APPLICATION, USE A SUITABLE CLEANING COMPOUND LIKE OUR BOTANICAL DISINFECTANT SOLUTION OR BOTANICAL CLEANER & SEALER AND ALLOW TO DRY. ALWAYS BE CAREFUL NOT TO TEAR OR LOOSEN LINERS IF PRESENT.

**APPLICATION:** ALWAYS ENSURE ADEQUATE VENTILATION. HVAC SYSTEM MUST BE UNDER NEGATIVE AIR PRESSURE DURING AND AFTER APPLICATION TO EXHAUST ODORS AND ALLOW FOR RAPID DRYING OF THE COATING. APPLY TO ALL SURFACES BY BRUSH, ROLLER, OR AIRLESS SPRAYER. BRUSHING OR ROLLING WILL REQUIRE 2 COATS APPLIED AT 90° TO EACH OTHER. SPRAY APPLICATIONS CAN BE COMPLETED WITH ONE COAT IN MOST CIRCUMSTANCES, BUT EXTREMELY POROUS AND/OR IRREGULAR SURFACES MAY REQUIRE A SECOND COAT TO ACHIEVE THE SMOOTH FINISHED SURFACE FOR OPTIMAL PERFORMANCE. FOR AIRLESS SPRAYER APPLICATIONS A 0.021-0.025 FLUID TIP SHOULD YIELD THE BEST RESULTS. DUE TO THE THICKER APPLICATION YOU CAN EXPECT A COVERAGE RATE 100-200 FT<sup>2</sup>/GAL AND WILL BE DRY TO THE TOUCH WITHIN 1 HOUR AND MAYBE RECOATED IN 2 HOURS. FULL ADHESION AND HARDNESS DEVELOPS IN 7 DAYS. **NOTE:** CIRCULATE FRESH DRY AIR THROUGHOUT THE SYSTEM AND AREA DURING APPLICATION AND AS LONG AFTER AS POSSIBLE. EXHAUST CIRCULATED AIR OUTSIDE THE BUILDING OR OCCUPIED SPACE, IF POSSIBLE. IF AIR MUST BE EXHAUSTED INSIDE THE BUILDING, CIRCULATE AIR THROUGH A FILTRATION SYSTEM WITH ODOR ABSORBING MEDIUM TO REDUCE THE LATEX ODORS FROM THE APPLICATION AREA. THIS CIRCULATION HELPS TO REDUCE THE DRY TIME OF THE COATING. **MAINTENANCE:** NORMAL CLEANING PROCEDURES MUST BE MAINTAINED IN HVAC SYSTEMS TO REMOVE ACCUMULATED AIRBORNE PARTICLES. WASH DOWN PERIODICALLY WITH MILD DETERGENT AND WATER. IF COATING BECOMES DAMAGED CLEAN SURFACE AND RE-APPLY COATING. **FIRST AID: INGESTION:** IF SWALLOWED, WASH OUT MOUTH WITH WATER. DO NOT INDUCE VOMITING UNLESS TOLD TO DO SO BY A DOCTOR OR PROFESSIONAL HEALTHCARE PROVIDER. IF SPONTANEOUS VOMITING OCCURS, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQUID INTO THE LUNG. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. **SKIN CONTACT:** IN CASE OF ACCIDENTAL SKIN CONTACT, REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND PLENTY OF WATER FOR 15 MINUTES. WASH CONTAMINATED CLOTHING BEFORE REUSE. IF IRRITATION OR ALLERGIC REACTION OCCURS GET MEDICAL ADVICE. **INHALATION:** NO IRRITATION EXPECTED; HOWEVER, IF IRRITATION OCCURS, MOVE INDIVIDUAL AWAY FROM EXPOSURE AND INTO FRESH AIR. IF BREATHING IS IRREGULAR OR STOPPED, ADMINISTER ARTIFICIAL RESPIRATION. IN CASE OF SHORTNESS OF BREATH, GIVE OXYGEN. CALL A PHYSICIAN IMMEDIATELY. **EYE CONTACT:** IF IN EYES, RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES IF EASY TO DO. CONTINUE RINSING. IF EYE IRRITATION PERSISTS, GET MEDICAL ATTENTION/ADVICE.

MADE IN USA  
QUESTIONS? Talk to us.  
bioesquesolutions.com

Distributed by NatuReal, LLC  
2091 NE 36th Street #50548  
Lighthouse Point, FL 33074  
800.921.4634



NON-FLAMMABLE

KEEP OUT OF REACH OF CHILDREN  
NET CONTENTS: 1 GALLON (3.78 L)

**WARNING:** KEEP OUT OF REACH OF CHILDREN. USE ONLY AS DIRECTED. INTENTIONAL MISUSE CAN BE HARMFUL OR FATAL. CAUSES SERIOUS EYE IRRITATION. FOR EMERGENCY MEDICAL ASSISTANCE, CALL YOUR LOCAL POISON CONTROL CENTER OR INFOTRAC (800) 535-5053. **STORAGE:** KEEP OUT OF REACH OF CHILDREN. KEEP FROM FREEZING. PRODUCT IS NON-COMBUSTIBLE. DISPOSAL: DISPOSAL OF CONTENTS/CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT IN ACCORDANCE WITH APPLICABLE LOCAL/REGIONAL/NATIONAL AND INTERNATIONAL REGULATIONS AND PRODUCT CHARACTERISTICS AT TIME OF DISPOSAL. **CA PROP 65:** THIS PRODUCT CONTAINS CHEMICALS (TITANIUM DIOXIDE PIGMENT) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER. FOR MORE INFORMATION GO TO WWW.P65WARNINGS.CA.GOV

4.9063"