



Guillemin / DSP Coupling & Adaptors

Our Guillemin / DSP couplings and adaptors are a French two claw symmetrical hermaphrodite connection system. There are two systems - Guillemin and DSP, which are both interchangeable but are used in different applications.

Guillemin is predominantly used in the industrial sector. DSP is used by the Fire Brigades.

CAPS:

Blanking caps are available with keep chains as standard and can be supplied with or without locking ring.

WASHERS & SPANNERS:

NBR washers for all DN sizes. A universal spanner for connecting couplings DN20-DN120.

MATERIALS: As Standard - Light Alloy
Brass
On request - Stainless Steel
Gun Metal

GUILLEMIN

DN Size	ka (mm-lug distance)	Hose Tail (mm)	Male BSP (inch)	Female BSP (inch)
20	32	25	¾	¾
25	37.5	x	1	1
40	55	40, 45	1 ½	1 ½
50	69	55	2	2
65	84	70	2 ½	2 ½
80	103	x	3	3
100	123	100	4	4
150	190	152	x	6

DSP

DN Size	ka (mm-lug distance)	Hose Tail (mm)	Male BSP (inch)	Female BSP (inch)
40	55	38, 45	1 ½	1 ½
65	84	70	2, 2 ½	2, 2 ½
100	123	x	4	4