



### **GOST**

DN Size	ka (mm- lug distance)	Hose Tail (mm)	Male BSP (inch)	Female BSP (inch)
50	78	25	1 ½	2
		38	2	2 ½
		52		
70	95	52	2 ½	2
		64		2 ½
		75		
80	107	64	2 ½	2 ½
		75	3	
100	140	100	4	4
				4 ½
125	166	125	5	5
150	187	150	6	6

## **ROTTA**

DN Size	ka (mm- lug distance)	Hose Tail (mm)	Male BSP (inch)	Female BSP (inch)
50	68	38	1 ½	1 ½
		52	2	2
70	85	52	2	2
		64	2 ½	2 ½

# Rotta & Gost Coupling & Adaptors

Our Rotta and Gost couplings and adaptors are
Russian 16 bar coupling systems. Both couplings
have a symmetrical two claw hermaphrodite connection
system but unlike the Gost system Rotta comes with
two interlocking swivel lugs.

#### **OPTIONS:**

Hose Tails, BSP threaded adaptors and reducers.

**Gost:** This is a symmetrical two claw hermaphrodite connection system.

**Rotta:** This is again a symmetrical two claw hermaphrodite connection system but unlike the Gost system, comes with two interlocking swivel lugs.

## **CAPS:**

Caps are available to blank off all DN connection sizes and come without keep chain

#### **WASHERS & WRENCHES:**

NBR Washers can be supplied for all DN sizes.

A universal spanner for DN50-DN100 can be supplied for the connection of couplings and adaptors.

MATERIALS: Gost - Aluminium

Gun Metal

Rotta - Gun Metal





Rotta & Gost cap in gun metal

Washers

