

Doulton® Water Filters

Operating and Exchange Instructions

For Ultracarb® Cartridges. Part No. W9123053

For Use in QT Ultracarb® Inline and HIP/Ultracarb® Inline Filter Systems

Cartridge Capacity: 2300 litres (600 gallons)
Rated Service Flow: 1.9 litres/min. (0.5 gallons/min)

Tested and Certified by NSF International against NSF/ANSI Standards 42 and 53 in QT Ultracarb® Inline and HIP/Ultracarb® Inline for the reduction of:

- Chlorine Reduction ; Taste & Odour
- Nominal Particulate reduction; Class 1
- Turbidity reduction
- Cyst reduction (including Giardia and live Cryptosporidium)
- Lead

Do not use where water is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems Certified for Cyst Reduction may be used on disinfected water that may contain filterable Cysts.

1 Installation/Replacement

General removal and re-installation of the cartridge is carried out as follows: (For full detailed instructions see installation instructions supplied with filter system).

HIP/Ultracarb® Inline Systems

With the water supply off, vent any pressure by opening the user tap. Unscrew the filter body. Care should be taken as it will be full of water. The cartridge can now be unscrewed from the cap and be replaced or cleaned in accordance with Section 4. To replace the cartridge place the cartridge O-Ring onto the threaded nipple and screw the thread into the cap until resistance is felt.

N.B. Do not over-tighten. The body can now be screwed into the cap. **Hand tighten only.**

Manufactured by:

Doulton Water Filters, Newcastle, Staffordshire, ST5 9BT, United Kingdom.

Telephone: +44 (0) 1782 664420

Fax: +44 (0) 1782 664490

Email: filtersales@doulton.com

Website: www.doulton.com

Doulton® and Ultracarb® are trademarks registered to Fairey Industrial Ceramics Limited.

QT Ultracarb® Inline Systems

The filter is designed so that the cartridge can be removed for cleaning or replacement by disengaging the filter body from the head and unscrewing the cartridge. See installation instructions for full details. Cleaning is a simple operation. The surface of the cartridge can be scrubbed with a stiff brush to restore the flow. Re-installation can be carried out by screwing the cartridge into the cap and following steps 10-15 of the installation instructions.

2 Conditioning the Cartridge

In order to remove any loose particles resulting from the manufacture of the cartridge, the water from the filter should be run to waste for 10 minutes. Additionally, to allow the filter to be conditioned to the source water, allow the unit to stand unused for a further 24 hours and then flush for a further 10 minutes to waste. The filter is now ready for use.

3 General Use

The filtered water can now be used for drinking and preparing food. The recommended flow rate should be used to give optimum performance. If the filter has been standing unused for 24 hours, one to two litres of water should be run to waste to ensure that the water is "fresh".

4 Cleaning the Filter

Due to filtration of particulate contaminants from the water during use, the flow of water from the filter may reduce over a period of time.

To return the water flow to its normal level, simply remove, clean and replace the cartridge as follows. Remove the cartridge in accordance with the filter installation instruction taking care at all times not to contaminate the inside of the cartridge or the end of the nipple with unfiltered water or dirty hands. Take the cartridge to a sink. Hold the cartridge under running water and scour with a stiff brush or kitchen scouring pad. The cartridge is now ready for replacement into the filter housing in accordance with the filter installation instructions or Section 1.

Authenticate and Register your Doulton® Drinking Water Filter

The unique 10 digit authenticity code printed on your Doulton® water filter enables you to authenticate and register your product directly with Doulton®.

This gives you the reassurance that you have purchased a genuine Doulton® product that has been precision made, in England, to the highest standards.

Authenticity and registration of your Doulton® water filter can be completed online by visiting:

www.doulton.com



Unique
Authenticity
Code

Product
Reference
Code

To ensure an accurate match with the Doulton® database please, carefully, input both the Product Reference Code and the Unique Authenticity Code (indicated above) and follow the instructions on screen.

LEGAL DISCLAIMER.

In the absence of any negligence or other breach of duty by us, the installation and use of this product is entirely at your own risk. You must at all times observe and comply with our instructions (whether set out in the appliance manual or otherwise) relating to the installation and use of this product. We will not be liable nor responsible to you for any loss or damage, legal disputes or conflicts of interests and other adverse events you suffer as a result of your failure to observe or comply with our instructions or otherwise results from your misuse or irresponsible or negligent use of the product or as a result of any events outside of our control. To the maximum extent permitted by any applicable laws, we make no warranty, representation or guarantee (whether express, implied or otherwise) regarding the fitness, merchantability, or suitability of this product for any unreasonable or unforeseeable purpose. This disclaimer does not affect your statutory consumer rights or otherwise restrict or limit any liability that we cannot lawfully exclude under any applicable laws.

AUTHENTICITY
GUARANTEE

