

Safety Data Sheet

91134 Trim Clean™

Stoner

Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. IDENTIFICATION

Stoner Incorporated
1070 Robert Fulton Hwy.
Quarryville, PA 17566
1-800-227-5538

Product Name: Trim Clean™
Product Code: 91134
Product Use: Cleaner
24-hour emergency phone: 1-800-424-9300 [CHEMTREC]

2. HAZARD IDENTIFICATION

POTENTIAL HEALTH EFFECTS

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols



GHS Classification

Gases under pressure - Liquefied Gas
Serious Eye Damage/Eye Irritation Category 1

Signal Word

Danger

Hazard Statements

Contains gas under pressure; may explode if heated.
Causes serious eye damage.

Precautionary Statements

Prevention

Wear protective gloves/protective clothing/eye protection/face protection.

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a poison center, doctor or medical center.

Storage

Protect from sunlight. Store in a well-ventilated place.

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>COMPONENT</u>	<u>CAS #</u>	<u>Percent</u>
Hydrocarbon propellant	68476-86-8	1 - 20
Anionic surfactant	577-11-7	1 - 20
Glycol ether	111-76-2	0.5 - 1.5
Organic acid	Mixture	0.1 - 0.99
Salts	7632-00-0	0.1 - 0.99

HMS® III* HAZARDOUS WARNINGS:

Health: 2	Flammability: 2	Physical: 0	Personal Protective Equipment:	See Section 8
-----------	-----------------	-------------	--------------------------------	---------------

* See www.paint.org/hmis or call the ACA at 1 (202) 462-6272 for more information on this current rating system.

4. FIRST AID MEASURES

Eyes: Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.

Skin Contact: In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if symptoms persist. Wash clothing before reuse. For liquid contact, treat for frostbite if necessary.

Ingestion: Ingestion is an unlikely route of exposure. Contact a physician, medical facility, or poison control center for advice on whether to induce vomiting.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep the victim warm and

quiet. Seek immediate medical attention.

NOTES TO PHYSICIAN:

Simple asphyxiant/Frost bite. No additional first aid information available. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: lung (for example, asthma-like conditions); liver; kidney;

5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards: This product contains a component(s) that is considered an extremely flammable gas(es), which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point.

Fire Fighting Instructions: Use CO₂, foam or dry chemical. Water is generally not effective and may spread fire; however, water spray may be used from a safe distance to cool closed containers and protect surrounding area.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Ventilate contaminated area. Avoid run-off into storm sewers and ditches which may lead to natural waterways. If runoff occurs, notify authorities as required. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly. Place waste material into container and close it tightly. Dispose of container properly.

7. HANDLING AND STORAGE

Handling: This material can be harmful or irritating. Use with adequate ventilation. Normal precautions common to safe manufacturing practice should be followed in handling and storage. Avoid prolonged or repeated breathing of vapor. Avoid prolonged or repeated contact with skin. Wash hands thoroughly after handling. If ventilation is not sufficient, wear proper respiratory equipment. Do not use near ignition sources.

Storage: Do not store at temperatures above 122 degrees F. Store away from incompatible materials such as materials that support combustion (oxidizing materials) and corrosive materials (strong acids or bases). Keep from freezing. Store at temperatures between 45° and 99° F. Normal precautions common to safe manufacturing practice should be followed in handling and storage. Store in a cool, dry, well ventilated area away from all sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Ventilation is required to maintain operator exposure below published exposure limits. Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the SDS (from known, suspected or apparent adverse effects). Local exhaust should be used in areas where exposure limits may be exceeded.

Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Have an eye wash station available.

Skin Protection: The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.

Respiratory Protection: Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol.

<u>COMPONENT</u>	<u>CAS #</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Hydrocarbon propellant	68476-86-8	1000ppm	Not established	Not established
Anionic surfactant	577-11-7	Not established	Not established	10 mg/m ³ TWA (WEEL)
Glycol ether	111-76-2	20 ppm [skin]	Not established	Not established
Organic acid	Mixture	Not established	Not established	Not established
Salts	7632-00-0	Not established	Not established	Not established

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Aerosol can	Lower Flammability Limit (%):	Not applicable
Appearance:	Clear Colorless	Upper Flammability Limit (%):	Not applicable
Odor:	None to very faint	Vapor Pressure (PSIG @ 70°F):	No data available
Odor Threshold:	None	Vapor Density [air = 1]:	>1
pH:	10 - 11.5	Relative Density (H ₂ O=1):	0.99
Melting/Freezing Point (°F):	No data available	Solubility in Water:	Complete; 100%
Boiling Point (°F):	No data available	Partial Coefficient: n-octanol/water:	No data available
Flash Point (°F PMCC):	Not applicable	Autoignition Temperature (°F):	Not applicable
Evaporation Rate:	0.02-0.1 (n-Butyl acetate = 1)	Decomposition Temperature (°F):	No data available
Flammability (solid, gas):	No data available	Viscosity, dynamic (cSt):	No data available
Percent VOCs (%):	1-20		

10. STABILITY AND REACTION

Chemical Stability: Stable.

Conditions to Avoid: Avoid contact with: Strong oxidizing agents. Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces. Strong alkalis.

Decomposition Products: Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Oxides of sulfur.

