# Safety Data Sheet 92303 Hybrid Ceramic Universal Sealant



Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

## 1. IDENTIFICATION

Stoner Incorporated 1070 Robert Fulton Hwy. Quarryville, PA 17566 1-800-227-5538	Product Name:Hybrid Ceramic UniversalProduct Code:92303Product Use:Automotive Appearance24-hour emergency phone:1-800-424-9300 [CHEM]							
	2. HAZARD IDENTIFICATION							
POTENTIAL HEALTH EFFECTS Classification of the chemical in accorda GHS Hazard Symbols	ace with paragraph (d) of §1910.1200;							
GHS Classification	Flammable Liquid Category 2							
Signal Word	Danger							
Hazard Statements	Highly flammable liquid and vapour.							
Precautionary Statements								
Prevention	Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. P241 - Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection.							
Response	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P370+P378 - In case of fire: Use proper media to extinguish.							
Storage	Keep container tightly closed. Store in a well-ventilated place. Keep cool.							
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.							

3. COMPOSI	ITION/INFORMATION ON INGREDIENTS				
COMPONENT Petroleum naphtha	a <u>CAS #</u> 64741-66-8	<u>Perce</u> 1 - 5	<u>nt</u>		
HMIS® III* HAZ Health: 2	ARDOUS WARNINGS: Flammability: 3	Physical: 0	Personal See Section 8 Protective Equipment:		
* See www.paint.or	rg/hmis or call the ACA at 1 (202) 462-6272 for more information	on this current rating system.			
4. FIRST AII	D MEASURES				
Eyes:	Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there				

is visual difficulty, seek medical attention. Skin Contact: In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if symptoms persist. Wash clothing before reuse.

*92303* 

PAGE 1

Ingestion:

Inhalation:

Do not induce vomiting. Aspiration into the lungs can cause serious damage. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. Contact a physician, medical facility, or poison control center immediately. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek immediate medical attention.

### NOTES TO PHYSICIAN:

This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin;

# 5. FIRE FIGHTING MEASURES Fire and/or Explosion Hazards: This product contains a component(s) that is considered a flammable liquid, which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. Fire Fighting Instructions: Use water spray, foam, dry chemical, or CO2. Fire fighters should wear normal protective equipment and positive-pressure self-contained breathing apparatus. Do not direct a solid stream of water or foam into hot burning pools, this may cause frothing and increase fire intensity.

### 6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Ventilate contaminated area. Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Avoid run-off into storm sewers and ditches which may lead to natural waterways. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly.

### 7. HANDLING AND STORAGE

Handling: Do not use near ignition sources. Avoid prolonged or repeated breathing of vapor. Avoid prolonged or repeated contact with skin. Avoid contact with eyes. Wash hands thoroughly after handling.
 Storage: Keep container tightly closed when not in use. Store in a cool, dry, well ventilated area away from all sources of ignition. Empty container may contain residues which are hazardous. Normal precautions common to safe manufacturing practice should be followed in handling and storage.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls:	Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the SDS (from				
	known, suspected or apparent adverse effects).				
Eye Protection:	Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as				
-	chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or				
	airborne material. Have an eye wash station available.				
Skin Protection:	The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with				
	skin.				
Respiratory Protection:	A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits. Use NIOSH approved				
respirator where there is likelihood of inhalation of the product mist, spray or aerosol.					
COMPONENT	CAS # ACGIH TLV OSHA PEL OTHER				

Not established

Not established

281ppm -mfr.

recommended

Petroleum naphtha

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Bulk liquid Lower Flammability Limit (%): Not applicable	
Appearance: Blue Upper Flammability Limit (%): Not applicable	
Odor: Fruity Vapor Pressure (PSIG @ 70°F): No data available	;
Odor Threshold:     Moderate     Vapor Density [air = 1]:     >1	
pH: Not applicable Relative Density (H2O=1): 0.99	
Melting/Freezing Point (°F): No data available Solubility in Water: Complete; 100%	
Boiling Point (°F): No data available Partial Coefficient: n- No data available octanol/water:	;
Flash Point (°F PMCC):     66.2     Autoignition Temperature (°F):     Not applicable	
Evaporation Rate: No data available Decomposition Temperature (°F): No data available	;
Flammability (solid, gas): No data available Viscosity, dynamic (cSt): No data available	;
Percent VOCs (%): 1 - 5	

# **10. STABILITY AND REACTION**

 Chemical Stability:
 Stable.

 Conditions to Avoid:
 Avoid contact with: Strong oxidizing agents. Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces.

 Decomposition Products:
 Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Oxides of siloxanes.

 Formaldehyde. When heated to temperatures above 150°C in the presence of air, one of the ingredients in this product can form formaldehyde vapors. Formaldehyde vapor is harmful by inhalation; irritating to eyes; sensitizer to the

# 11. TOXICOLOGICAL INFORMATION

Reproductive & Developmental Toxicity: IARC Carcinogen Designation:

No data available.

signation: No data available

Stoner Incorporated

92303

64741-66-8

respiratory system; an acute toxicant and a potential cancer hazard at concentrations greater than 0.75 ppm.

<b>Ingredient</b> Petroleum naphtha		<b>CAS #</b> 64741-66-8	<b>Toxicological Data</b> Dermal LD50 Rabbit > 3160 mg/kg Oral LD50 Rat > 10000 mg/kg			
NJ Trade Secret Registry		MIXTURE	No data available Dermal LD50 Rat > 2000 mg/kg Oral LD50 Rat > 2000 mg/kg Inhalation LC50 (4h) Rat 2 MG/L			
12. ECOLO	GICAL INFORMA	TION				
Ecological Toxic Mobility: Degradability:	No data	ise long-term adverse effects in the aquatic e available duct is expected to be inherently biodegrada				
<b>Ingredient</b> No data available		CAS #	Toxicological Data			
13. DISPOS	AL CONSIDERATI	IONS				
Disposal :	Dispose according to Feder	ral, State and local regulations.				
14. TRANSI	PORTATION INFO	RMATION				
DOT UN IATA UN IMDG UN	268         Petro           268         Petro           268         Petro           268         Petro	er Shipping name leum distillates, n.o.s. (contains Octanes)† leum distillates, n.o.s. (contains Octanes)† leum distillates, n.o.s. (contains Octanes)† or this transportation mode.	Hazard Class 3 3 3	Packing Group II II II		
15. REGULATORY INFORMATION						
Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:         COMPONENT       CAS #       % BY WEIGHT       Regulatory Body         No components listed in this section.       SARA Section 313						

### **Toxic Substances Control Act**

All components of this product are listed on the TSCA inventory.

### California Prop 65

This product contains no California Proposition 65 ingredients that cause cancer, birth defects or other reproductive harm.

# **16. OTHER INFORMATION**

Other Information : SDS Prepared by L. Dean Swartz, SDS Coordinator

Version Date: 07/25/22

This information contained in this SDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.