

Safety Data Sheet

99076 Auto Care Kit



Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. IDENTIFICATION

Stoner Incorporated
1070 Robert Fulton Hwy.
Quarryville, PA 17566
1-800-227-5538

Product Name: Auto Care Kit
Product Code: 99076
Product Use: Auto Clean & Detailing
24-hour emergency phone: 1-800-424-9300 [CHEMTREC]

This product kit contains the following Stoner products:

- 91164- Invisible Glass®
- 91134- Trim Clean™
- 91094- More Shine™ Tire Finish
- 91154- Tar & Sap Remover

Safety Data Sheet

91164 Invisible Glass®

Stoner

Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. IDENTIFICATION

Stoner Incorporated
1070 Robert Fulton Hwy.
Quarryville, PA 17566
1-800-227-5538

Product Name: Invisible Glass®
Product Code: 91164
Product Use: Glass Cleaner
24-hour emergency phone: 1-800-424-9300 [CHEMTREC]

2. HAZARD IDENTIFICATION

POTENTIAL HEALTH EFFECTS

Classification of the chemical in accordance with paragraph (d) of §1910.1200;
GHS Hazard Symbols



GHS Classification

Gases under pressure - Liquefied Gas
Serious Eye Damage/Eye Irritation Category 2A

Signal Word

Warning

Hazard Statements

Contains gas under pressure; may explode if heated.
Causes serious eye irritation.

Precautionary Statements

Prevention

P264 - Wash thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.

Storage

Protect from sunlight. Store in a well-ventilated place.

3. COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT	CAS #	Percent
Water	7732-18-5	80 - 100
Hydrocarbon propellant	68476-86-8	1-20
Proprietary hydrocarbon blend	Trade Secret	1-15

HMIS® III* HAZARDOUS WARNINGS:

Health: 2

Flammability: 2

Physical: 0

Personal Protective Equipment:

See Section 8

* See www.paint.org/hmis or call the ACA at 1 (202) 462-6272 for more information on this current rating system.

4. FIRST AID MEASURES

Eyes: Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.

Skin Contact: In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if symptoms persist. Wash clothing before reuse. For liquid contact, treat for frostbite if necessary.

Ingestion: Contact a physician, medical facility, or poison control center immediately.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Continue your efforts until help arrives or the victim starts to breathe on his own. Do not leave victim alone. Seek immediate medical attention. Keep the victim warm and quiet.

NOTES TO PHYSICIAN:

Simple asphyxiant/Frost bite. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin; lung (for example, asthma-like conditions); liver; kidney; blood forming system;

5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards: Product is water based material, containing minor amounts of flammable ingredients. This product contains a component(s) that is considered a flammable liquid, which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. This product contains a component(s) that is considered an extremely flammable gas(es), which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point.

Fire Fighting Instructions: Use alcohol foam, water fog, dry chemical, or CO₂. Water is generally not effective and may spread fire; however, water spray may be used from a safe distance to cool closed containers and protect surrounding area.

6. ACCIDENTAL RELEASE MEASURES**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:**

Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Ventilate contaminated area. Avoid run-off into storm sewers and ditches which may lead to natural waterways. If runoff occurs, notify authorities as required. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly.

7. HANDLING AND STORAGE

Handling: Do not use near ignition sources. If ventilation is not sufficient, wear proper respiratory equipment. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of vapor. Do not store containers in excessive heat or direct sunlight. Protect container against physical damage. Use with adequate ventilation. This material can be harmful or irritating. Normal precautions common to safe manufacturing practice should be followed in handling and storage. Do not use near ignition sources. Protect container against physical damage.

Storage: Store in a cool, dry, well ventilated area away from all sources of ignition. Normal precautions common to safe manufacturing practice should be followed in handling and storage. Do not store at temperatures above 122 degrees F. Store away from incompatible materials such as materials that support combustion (oxidizing materials) and corrosive materials (strong acids or bases). Empty container may contain residues which are hazardous.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the SDS (from known, suspected or apparent adverse effects). Local exhaust should be used in areas where exposure limits may be exceeded. Ventilation is required to maintain operator exposure below published exposure limits.

Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Have an eye wash station available.

Skin Protection: The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.

Respiratory Protection: A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits. Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol.

<u>COMPONENT</u>	<u>CAS #</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Water	7732-18-5	Not established	Not established	Not established
Hydrocarbon propellant	68476-86-8	1000ppm	Not established	Not established
Proprietary hydrocarbon blend	Trade Secret	20 ppm	50ppm	Not established

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Aerosol can	Lower Flammability Limit (%):	Not applicable
Appearance:	Clear Colorless	Upper Flammability Limit (%):	Not applicable
Odor:	Alcohol	Vapor Pressure (PSIG @ 70°F):	53.00
Odor Threshold:	Mild	Vapor Density [air = 1]:	>1
pH:	Not applicable	Relative Density (H ₂ O=1):	0.96
Melting/Freezing Point (°F):	No data available	Solubility in Water:	Not determined
Boiling Point (°F):	No data available	Partial Coefficient: n-octanol/water:	No data available
Flash Point (°F PMCC):	Not applicable	Autoignition Temperature (°F):	869
Evaporation Rate:	Not determined	Decomposition Temperature (°F):	No data available
Flammability (solid, gas):	No data available	Viscosity, dynamic (cSt):	No data available
Percent VOCs (%):	1-20		

10. STABILITY AND REACTION

Chemical Stability: Stable.

Conditions to Avoid: Avoid contact with: Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces. Acids. Strong oxidizing agents. Acetaldehyde. Chlorine. Ethylene oxide. Isocyanates. Strong alkalis.

Decomposition Products: Burning can produce the following combustion products: Carbon dioxide and carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Inhalation Toxicity: High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.

Reproductive & Developmental Toxicity: No data available.

IARC Carcinogen Designation: No data available

Ingredient

Proprietary hydrocarbon blend

CAS

Trade Secret

Toxicological Data

DERMAL LD50 Rabbit 220 mg/kg
ORAL LD50 GUINEA PIG 1200 mg/kg
ORAL LD50 Rat 250 mg/kg
INHALATION LC50 Rat 2900 MG/M3
INHALATION LC50 Mouse 700 ppm
INHALATION LC50 Mouse 3380 MG/M3
DERMAL LD50 Rabbit 12800 mg/kg
ORAL LD50 Mouse 3600 mg/kg
ORAL LD50 Rat 5000 mg/kg
INHALATION LC50 Rat 16000 ppm
INHALATION LC50 Mouse 53000 MG/M3

Isopropanol

12. ECOLOGICAL INFORMATION

Ecological Toxicity: No data available

Mobility: No data available This material (or one of its components), dissolves in water. If it enters the soil, it will be highly mobile and may contaminate ground water.

Degradability: No data available.

Ingredient

Proprietary hydrocarbon blend

CAS

Trade Secret

Toxicological Data

Aquatic LC50 (96h) MINNOW = 72860 mg/L
Aquatic LC50 (48h) Daphnia > 100 mg/L
Aquatic LC50 (96h) Algae 6500 - 13000 mg/L
Aquatic LC50 (96h) MINNOW = 9640 mg/L
24HR EC50 Daphnia > 10000 mg/L
No data available

Dimethyl carbinol

13. DISPOSAL CONSIDERATIONS

Disposal : Dispose according to Federal, State and local regulations.

14. TRANSPORTATION INFORMATION

Agency	UN Number	Proper Shipping name	Hazard Class	Packing Group
DOT	UN1950	Aerosols, Non- Flammable†	2.2	Not applicable
IATA	ID8000	Consumer Commodity†	9	Not applicable
IMDG	UN1950	Aerosols, Non- Flammable†	2.2	Not applicable

† "Limited Quantities" may be applicable for this transportation mode.

15. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

COMPONENT	CAS #	% BY WEIGHT	Regulatory Body
No components listed in this section.			

Toxic Substances Control Act

All components of this product are listed on the TSCA inventory.

California Prop 65

This product contains no California Proposition 65 ingredients that cause cancer, birth defects or other reproductive harm.

16. OTHER INFORMATION

Other Information : SDS Prepared by L. Dean Swartz, SDS Coordinator

Version Date: 10/01/2021

This information contained in this SDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.

Safety Data Sheet
91034 Trim Shine®

Stoner

Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. IDENTIFICATION

Stoner Incorporated
 1070 Robert Fulton Hwy.
 Quarryville, PA 17566
 1-800-227-5538

Product Name: Trim Shine®
 Product Code: 91034
 Product Use: Automotive Appearance
 24-hour emergency phone: 1-800-424-9300 [CHEMTREC]

2. HAZARD IDENTIFICATION

POTENTIAL HEALTH EFFECTS
 Classification of the chemical in accordance with paragraph (d) of §1910.1200;
 GHS Hazard Symbols



GHS Classification

Flammable Aerosol Category 1
 Gases under pressure - Liquefied Gas
 Aspiration Hazard Category 1
 Skin Corrosion/Irritation Category 2
 Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3

Signal Word

Danger

Hazard Statements

Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 May be fatal if swallowed and enters airways.
 Causes skin irritation.
 May cause drowsiness or dizziness.

Precautionary Statements

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Do not spray on an open flame or other ignition source.
 Pressurized container: Do not pierce or burn, even after use.
 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P264 - Wash thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/protective clothing/eye protection/face protection.

Response

P301+P310 - If swallowed: Immediately call a poison center, doctor or medical center.
 P302+P352 - If on skin: Wash with plenty of soap and water.
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P312 - Call a poison center, doctor or medical center if you feel unwell.
 P321 - Specific treatment (see on this SDS).
 Do NOT induce vomiting.
 If skin irritation occurs: Get medical advice/attention.

Storage

Store in a well-ventilated place. Keep container tightly closed.
 Store locked up.
 Protect from sunlight. Store in a well-ventilated place.
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

3. COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT	CAS #	Percent		
Aliphatic hydrocarbons	142-82-5	40 - 60		
Hydrocarbon propellant	68476-86-8	20 - 40		

HMIS® III* HAZARDOUS WARNINGS:

Health: 1	Flammability: 4	Physical: 0	Personal Protective Equipment:	See Section 8
-----------	-----------------	-------------	--------------------------------	---------------

* See www.paint.org/hmis or call the ACA at 1 (202) 462-6272 for more information on this current rating system.

4. FIRST AID MEASURES

Eyes:	Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.
Skin Contact:	In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if symptoms persist. Wash clothing before reuse. For liquid contact, treat for frostbite if necessary.
Ingestion:	Do not induce vomiting. Aspiration into the lungs can cause serious damage. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. Contact a physician, medical facility, or poison control center immediately.
Inhalation:	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

NOTES TO PHYSICIAN:

Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used only in situations of emergency life support. This material is an aspiration hazard. Aspiration during swallowing or vomiting may severely damage the lungs. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin; lung (for example, asthma-like conditions); kidney; central nervous system; auditory system; arrhythmias (irregular heartbeats);

5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards:	This product contains a component(s) that is considered a flammable liquid, which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. This product contains a component(s) that is considered an extremely flammable gas(es), which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. "Empty" containers retain product residue and can be dangerous.
Fire Fighting Instructions:	Use CO2, foam or dry chemical. Fire fighters should wear normal protective equipment and positive-pressure self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Ventilate contaminated area. Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Avoid run-off into storm sewers and ditches which may lead to natural waterways. If runoff occurs, notify authorities as required. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly.

7. HANDLING AND STORAGE

Handling:	Do not use near ignition sources. Normal precautions common to safe manufacturing practice should be followed in handling and storage. This material can be harmful or irritating. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of vapor. Use with adequate ventilation. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death.
Storage:	Store in a cool, dry, well ventilated area away from all sources of ignition. Empty container may contain residues which are hazardous. Normal precautions common to safe manufacturing practice should be followed in handling and storage. Do not store at temperatures above 122 degrees F. Store away from incompatible materials such as materials that support combustion (oxidizing materials) and corrosive materials (strong acids or bases).

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls:	Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the SDS (from known, suspected or apparent adverse effects). Ventilation is required to maintain operator exposure below published exposure limits.
Eye Protection:	Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Have an eye wash station available.
Skin Protection:	The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.
Respiratory Protection:	A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits. Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol. No respiratory protection required under normal conditions of use.

COMPONENT	CAS #	ACGIH TLV	OSHA PEL	OTHER
Aliphatic hydrocarbons	142-82-5	400 ppm TWA	Not established	Not established
Hydrocarbon propellant	68476-86-8	1000ppm	Not established	Not established

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Aerosol can	Lower Flammability Limit (%):	Not applicable
Appearance:	Clear Colorless	Upper Flammability Limit (%):	Not applicable
Odor:	Light Hydrocarbon	Vapor Pressure (PSIG @ 70°F):	46.00
Odor Threshold:	Mild	Vapor Density [air = 1]:	>1
pH:	Not applicable	Relative Density (H ₂ O-1):	0.66
Melting/Freezing Point (°F):	No data available	Solubility in Water:	Negligible: 0-1%
Boiling Point (°F):	No data available	Partial Coefficient: n-octanol/water:	No data available
Flash Point (°F PMCC):	Not applicable	Autoignition Temperature (°F):	474.8
Evaporation Rate:	<0.020 (n-Butyl acetate = 1)	Decomposition Temperature (°F):	No data available
Flammability (solid, gas):	No data available	Viscosity, dynamic (cSt):	No data available
Percent VOCs (%):	80 - 100		

10. STABILITY AND REACTION

Chemical Stability:	Stable.
Conditions to Avoid:	Avoid contact with: Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces. Strong oxidizing agents.
Decomposition Products:	Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Various hydrocarbons. When heated to temperatures above 150°C in the presence of air, one of the ingredients in this product can form formaldehyde vapors. Formaldehyde vapor is harmful by inhalation; irritating to eyes; sensitizer to the respiratory system; an acute toxicant and a potential cancer hazard at concentrations greater than 0.75 ppm.

11. TOXICOLOGICAL INFORMATION

Reproductive & Developmental Toxicity:	No data available.
IARC Carcinogen Designation:	No data available

Ingredient	CAS #	Toxicological Data
Aliphatic hydrocarbons	142-82-5	INHALATION LC50 Rat 103 GM/M3

12. ECOLOGICAL INFORMATION

Ecological Toxicity:	No data available
Mobility:	No data available

Ingredient	CAS #	Toxicological Data
Aliphatic hydrocarbons	142-82-5	Aquatic LC50 (24h) Fish = 4 mg/L 48HR EC50 Daphnia = 1.5 mg/L 96HR EC50 Algae = 3.7 mg/L No data available

13. DISPOSAL CONSIDERATIONS

Disposal :	Dispose according to Federal, State and local regulations.
------------	--

14. TRANSPORTATION INFORMATION

Agency	UN Number	Proper Shipping name	Hazard Class	Packing Group
DOT	UN1950	Aerosols, Flammable†	2.1	Not applicable
IATA	ID8000	Consumer Commodity†	9	Not applicable
IMDG	UN1950	Aerosols, Flammable†	2.1	Not applicable

† "Limited Quantities" may be applicable for this transportation mode.

15. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

COMPONENT	CAS #	% BY WEIGHT	Regulatory Body
No components listed in this section.			SARA Section 313

Toxic Substances Control Act

All components of this product are listed on the TSCA inventory.

California Prop 65

This product contains no California Proposition 65 ingredients that cause cancer, birth defects or other reproductive harm.

16. OTHER INFORMATION

Other Information :	SDS Prepared by L. Dean Swartz, SDS Coordinator
---------------------	---

Version Date:	10/19/2021
---------------	------------

This information contained in this SDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.

Safety Data Sheet

91094 More Shine™ Tire Finish™

Stoner

Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. IDENTIFICATION

Stoner Incorporated
1070 Robert Fulton Hwy.
Quarryville, PA 17566
1-800-227-5538

Product Name: More Shine™ Tire Finish™
Product Code: 91094
Product Use: Tire Coating
24-hour emergency phone: 1-800-424-9300 [CHEMTREC]

2. HAZARD IDENTIFICATION

POTENTIAL HEALTH EFFECTS

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols



GHS Classification

Gases under pressure - Refrigerated Liquefied Gas
Aspiration Hazard Category 1
Flammable Aerosol Category 2
Serious Eye Damage/Eye Irritation Category 2A
Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3

Signal Word

Danger

Hazard Statements

Flammable aerosol.
Contains refrigerated gas; may cause cryogenic burns or injury.
May be fatal if swallowed and enters airways.
Causes serious eye irritation.
May cause drowsiness or dizziness.

Precautionary Statements

Prevention

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
Wear cold insulating gloves/face shield/eye protection.

Response

P301+P310 - If swallowed: Immediately call a poison center, doctor or medical center.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
P312 - Call a poison center, doctor or medical center if you feel unwell.
Get immediate medical advice/attention.
Do NOT induce vomiting.
Thaw frosted parts with lukewarm water. Do not rub affected area.
If eye irritation persists: Get medical advice/attention.

Storage

Store in a well-ventilated place.
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

3. COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT	CAS #	Percent
2-propanone	67-64-1	40 - 60
Methyl acetate	79-20-9	20 - 40
Aliphatic hydrocarbons	142-82-5	1-20
Propellant	124-38-9	1-20

HMTS® III* HAZARDOUS WARNINGS:

Health: 1	Flammability: 3	Physical: 0	Personal Protective Equipment:	See Section 8
-----------	-----------------	-------------	--------------------------------	---------------

* See www.paint.org/hmis or call the ACA at 1 (202) 462-6272 for more information on this current rating system.

4. FIRST AID MEASURES

Eyes:	Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.
Skin Contact:	In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if symptoms persist. Wash clothing before reuse. Wash the contaminated skin with soap and water. For liquid contact, treat for frostbite if necessary.
Ingestion:	Do not induce vomiting. Aspiration into the lungs can cause serious damage. Contact a physician, medical facility, or poison control center immediately. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs.
Inhalation:	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Continue your efforts until help arrives or the victim starts to breathe on his own. Do not leave victim alone. Seek immediate medical attention.

NOTES TO PHYSICIAN:

This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. Treatment is symptomatic and supportive. Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used only in situations of emergency life support. Aspiration during swallowing or vomiting may severely damage the lungs. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin; lung (for example, asthma-like conditions); liver; kidney; blood forming system; central nervous system; auditory system; arrhythmias (irregular heartbeats);

5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards:	This product contains a component(s) that is considered a flammable liquid, which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. Hazardous decomposition products may be formed (see Sec.10). "Empty" containers retain product residue and can be dangerous. Containers may rupture or explode under fire conditions.
Fire Fighting Instructions:	Use CO2, foam or dry chemical. Water is generally not effective and may spread fire; however, water spray may be used from a safe distance to cool closed containers and protect surrounding area.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Ventilate contaminated area. Avoid run-off into storm sewers and ditches which may lead to natural waterways. If runoff occurs, notify authorities as required. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly.

7. HANDLING AND STORAGE

Handling:	Do not use near ignition sources. If ventilation is not sufficient, wear proper respiratory equipment. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of vapor. Do not store containers in excessive heat or direct sunlight. Protect container against physical damage. Use with adequate ventilation. Normal precautions common to safe manufacturing practice should be followed in handling and storage. This material can be harmful or irritating. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death.
Storage:	Store in a cool, dry, well ventilated area away from all sources of ignition. Normal precautions common to safe manufacturing practice should be followed in handling and storage. Empty container may contain residues which are hazardous. Do not store at temperatures above 122 degrees F.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls:	Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the SDS (from known, suspected or apparent adverse effects). Local exhaust should be used in areas where exposure limits may be exceeded.
Eye Protection:	Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Have an eye wash station available.
Skin Protection:	The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.
Respiratory Protection:	A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits. Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol. No respiratory protection required under normal conditions of use.

COMPONENT	CAS #	ACGIH TLV	OSHA PEL	OTHER
2-propanone	67-64-1	500 ppm TWA	Not established	Not established
Methyl acetate	79-20-9	200 ppm TWA	200 ppm TWA	Not established
Aliphatic hydrocarbons	142-82-5	400 ppm TWA	Not established	Not established
Propellant	124-38-9	5000 ppm	5000 ppm	Not established

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Aerosol can	Lower Flammability Limit (%):	Not applicable
Appearance:	Clear Colorless	Upper Flammability Limit (%):	Not applicable
Odor:	Sweet odor Solvent	Vapor Pressure (PSIG @ 70°F):	53.0
Odor Threshold:	Moderate	Vapor Density [air = 1]:	>1
pH:	Not applicable	Relative Density (H ₂ O = 1):	0.88
Melting/Freezing Point (°F):	No data available	Solubility in Water:	Not determined
Boiling Point (°F):	No data available	Partial Coefficient: n-octanol/water:	No data available
Flash Point (°F PMCC):	Not applicable	Autoignition Temperature (°F):	474
Evaporation Rate:	Not determined	Decomposition Temperature (°F):	No data available
Flammability (solid, gas):	No data available	Viscosity, dynamic (cSt):	No data available
Percent VOCs (%):	1-20		

10. STABILITY AND REACTION

Chemical Stability:	Stable.
Conditions to Avoid:	Avoid contact with: Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces. Acids. Strong oxidizing agents. Sparks, open flame, other ignition sources, and elevated temperatures. Alkali. Alkaline earth metals. Metal acetylides. Chromium. Titanium above 550° C. Uranium above 750° C.
Decomposition Products:	Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. When heated to temperatures above 150°C in the presence of air, one of the ingredients in this product can form formaldehyde vapors. Formaldehyde vapor is harmful by inhalation; irritating to eyes; sensitizer to the respiratory system; an acute toxicant and a potential cancer hazard at concentrations greater than 0.75 ppm. Various hydrocarbons. Carbon Monoxide. Oxygen. Formaldehyde.

11. TOXICOLOGICAL INFORMATION

Reproductive & Developmental Toxicity:	No data available.	
IARC Carcinogen Designation:	No data available	
Ingredient	CAS #	Toxicological Data
2-propanone	67-64-1	DERMAL LD50 GUINEA PIG 9400 UL/KG ORAL LD50 Mouse 3 GM/KG
Aliphatic hydrocarbons	142-82-5	INHALATION LC50 Rat 50100 MG/M3
Propellant	124-38-9	INHALATION LC50 Rat 103 GM/M3 INHALATION LC50 Mouse 200000 ppm INHALATION LC50 Mouse 361 GM/M3 INHALATION LC50 Rat 470000 ppm

12. ECOLOGICAL INFORMATION

Ecological Toxicity:	No data available	
Mobility:	No data available	
Degradability:	No data available. This product is unlikely to biodegrade at a significant rate.	
Ingredient	CAS #	Toxicological Data
2-propanone	67-64-1	Aquatic LC50 (48h) Rainbow Trout = 6100 mg/L 48HR EC50 Daphnia = 7630 mg/L 96H EC50 PSEUDOKIRCHNERIELLA SUBCAPITATA 0.0209MG/
Aliphatic hydrocarbons	142-82-5	Aquatic LC50 (24h) Fish = 4 mg/L 48HR EC50 Daphnia = 1.5 mg/L 96HR EC50 Algae = 3.7 mg/L

Propellant

124-38-9

No data available
Aquatic LC50 (96h) Rainbow Trout 35 mg/L
No data available
No data available

13. DISPOSAL CONSIDERATIONS

Disposal : Dispose according to Federal, State and local regulations.

14. TRANSPORTATION INFORMATION

Agency	UN Number	Proper Shipping name	Hazard Class	Packing Group
DOT	UN1950	Aerosols, Flammable†	2.1	Not applicable
IATA	ID8000	Consumer Commodity†	9	Not applicable
IMDG	UN1950	Aerosols, Flammable†	2.1	Not applicable

† "Limited Quantities" may be applicable for this transportation mode.

15. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

COMPONENT	CAS #	% BY WEIGHT	Regulatory Body
No components listed in this section.			
SARA Section 313			

Toxic Substances Control Act

All components of this product are listed on the TSCA inventory.

California Prop 65

This product contains no California Proposition 65 ingredients that cause cancer, birth defects or other reproductive harm.

16. OTHER INFORMATION

Other Information : SDS Prepared by L. Dean Swartz, SDS Coordinator

Version Date: 10/06/2021

This information contained in this SDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.

Safety Data Sheet

91154 Tar & Sap Remover

Stoner

Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. IDENTIFICATION

Stoner Incorporated
1070 Robert Fulton Hwy.
Quarryville, PA 17566
1-800-227-5538

Product Name: Tar & Sap Remover
Product Code: 91154
Product Use: Bug & Tar Remover
24-hour emergency phone: 1-800-424-9300 [CHEMTREC]

2. HAZARD IDENTIFICATION

POTENTIAL HEALTH EFFECTS

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols



GHS Classification

Flammable Aerosol Category 1
Gases under pressure - Liquefied Gas
Skin Sensitisation Category 1
Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 2A
Carcinogenicity Category 2
Reproductive Toxicity Category 2
Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 2

Signal Word

Danger

Hazard Statements

Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
Harmful if inhaled.
Suspected of causing cancer.
Suspected of damaging fertility or the unborn child.
May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements

Prevention

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Do not breathe dust/fume/gas/mist/vapours/spray.
Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing should not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.

Response

P302+P352 - If on skin: Wash with plenty of soap and water.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If exposed or concerned: Get medical advice/attention.
P312 - Call a poison center, doctor or medical center if you feel unwell.
Get medical advice/attention if you feel unwell.
P321 - Specific treatment (see on this SDS).
If skin irritation occurs: Get medical advice/attention.
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Wash contaminated clothing before reuse.

Storage

Store locked up.
Protect from sunlight. Store in a well-ventilated place.
Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

3. COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT	CAS #	Percent
solvent naphtha (petroleum), heavy aliph.	64742-96-7	1-20
Distillates (petroleum), hydrotreated light	64742-47-8	1-20
Halogenated hydrocarbon	75-37-6	1-20
Glycol ether	112-34-5	7 - 13
Aliphatic hydrocarbons	142-82-5	5 - 10
Dimethyl carbinol	67-63-0	5 - 10
Petroleum hydrocarbon	1330-20-7	7 - 13
Citrus distillates	5989-27-5	1 - 5

HMS@ III* HAZARDOUS WARNINGS:

Health: 2*	Flammability: 4	Physical: 2	Personal Protective Equipment:	See Section 8
------------	-----------------	-------------	--------------------------------	---------------

* See www.paint.org/hmis or call the ACA at 1 (202) 462-6272 for more information on this current rating system.

4. FIRST AID MEASURES

Eyes:	Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.
Skin Contact:	In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if symptoms persist. Wash clothing before reuse.
Ingestion:	If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. Do not induce vomiting. Aspiration into the lungs can cause serious damage. Contact a physician, medical facility, or poison control center immediately. Have victim drink 8 to 10 ounces of water to dilute the material in the stomach.
Inhalation:	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek immediate medical attention. Keep the victim warm and quiet.

NOTES TO PHYSICIAN:

Inhalation of high concentrations of the material, or one of its components, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used only in situations of emergency life support. This material (or a component) may cause acidosis. This material is an aspiration hazard. Aspiration during swallowing or vomiting may severely damage the lungs. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin; lung (for example, asthma-like conditions); kidney; auditory system; arrhythmias (irregular heartbeats); liver; blood forming system; central nervous system;

5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards:	This product contains a component(s) that is considered a flammable liquid, which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. This product contains a component(s) that is considered an extremely flammable gas(es), which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. Containers may rupture or explode under fire conditions. "Empty" containers retain product residue and can be dangerous.
Fire Fighting Instructions:	Use CO2, foam or dry chemical. Fire fighters should wear normal protective equipment and positive-pressure self-contained breathing apparatus. Water is generally not effective and may spread fire; however, water spray may be used from a safe distance to cool closed containers and protect surrounding area.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Avoid run-off into storm sewers and ditches which may lead to natural waterways. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly. Remove all sources of ignition. Ventilate contaminated area. If runoff occurs, notify authorities as required.

7. HANDLING AND STORAGE

Handling: Do not use near ignition sources. Avoid prolonged or repeated breathing of vapor. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death. May cause frostbite. If ventilation is not sufficient, wear proper respiratory equipment. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of vapor. This material can be harmful or irritating. Do not use near ignition sources. Do not store containers in excessive heat or direct sunlight. Protect container against physical damage.

Storage: Store in a cool, dry, well ventilated area away from all sources of ignition. Keep away from heat, sparks and flame. Do not store at temperatures above 122 degrees F. Empty container may contain residues which are hazardous.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the SDS (from known, suspected or apparent adverse effects). Local exhaust should be used in areas where exposure limits may be exceeded.

Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Have an eye wash station available.

Skin Protection: The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.

Respiratory Protection: If respiratory irritation develops below the recommended exposure limits, use an NIOSH approved nuisance dust/mist/organic vapor respirator. A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits. Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol.

<u>COMPONENT</u>	<u>CAS #</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
solvent naphtha (petroleum), heavy aliph.	64742-96-7	Not established	Not established	Not established
Distillates (petroleum), hydrotreated light	64742-47-8	Not established	500 ppm	Not established
Halogenated hydrocarbon	75-37-6	Not established	Not established	1000ppm TWA (Mfr.)
Glycol ether	112-34-5	20ppm	50ppm	35ppm TWA (Mfg. recommend)
Aliphatic hydrocarbons	142-82-5	400 ppm TWA	Not established	Not established
Dimethyl carbinol	67-63-0	400 ppm	Not established	500 ppm STEL
Petroleum hydrocarbon	1330-20-7	150 PPM STEL; 651 MG/M3 STEL	Not established	100ppm
Citrus distillates	5989-27-5	20 ppm TWA	Not established	Not established

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Aerosol can	Lower Flammability Limit (%):	Not applicable
Appearance:	Clear Colorless	Upper Flammability Limit (%):	Not applicable
Odor:	Petroleum solvent	Vapor Pressure (PSIG @ 70°F):	No data available
Odor Threshold:	Mild	Vapor Density [air = 1]:	>1
pH:	Not applicable	Relative Density (H2O=1):	0.87
Melting/Freezing Point (°F):	No data available	Solubility in Water:	Not determined
Boiling Point (°F):	No data available	Partial Coefficient: n-octanol/water:	No data available
Flash Point (°F PMCC):	Not applicable	Autoignition Temperature (°F):	449
Evaporation Rate:	0.5-2 (n-Butyl acetate = 1)	Decomposition Temperature (°F):	No data available
Flammability (solid, gas):	No data available	Viscosity, dynamic (cSt):	No data available
Percent VOCs (%):	20 - 40		

10. STABILITY AND REACTION

Chemical Stability: Stable.

Conditions to Avoid: Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces. Avoid contact with: Strong oxidizing agents. Chlorine. Hypochlorites. Alkali. Alkaline earth metals. Powdered metals. Strong alkalis.

Decomposition Products: Acetaldehyde. Acids. Ethylene oxide. Isocyanates.

Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Aldehydes. Various hydrocarbons. This material can be decomposed by extremely high temperatures (open flames, glowing metal surfaces, etc.) forming hydrofluoric acid and carbonyl fluoride.

11. TOXICOLOGICAL INFORMATION

Inhalation Toxicity: High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.

Reproductive & Developmental Toxicity: No data available.

IARC Carcinogen Designation: No data available

Ingredient	CAS #
Distillates (petroleum), hydrotreated light	64742-47-8
Halogenated hydrocarbon	75-37-6
Petroleum hydrocarbon	1330-20-7
Glycol ether	112-34-5
Aliphatic hydrocarbons	142-82-5
Dimethyl carbinol	67-63-0
Petroleum hydrocarbon	100-41-4
Citrus distillates	5989-27-5

Toxicological Data

Dermal LD50 Rabbit > 2000 mg/kg
 Oral LD50 Rat > 5000 mg/kg
 No data available
 No data available
 ORAL ALD Rat > 1500 mg/kg
 4HR ALC Rat 383000 ppm
 Dermal LD50 Rabbit > 2000 mg/kg
 Oral LD50 Rat = 5000 mg/kg
 Inhalation LC50 Rat 5000 ppm
 Dermal LD50 Rabbit = 2700 mg/kg
 Oral LD50 Rat = 6560 mg/kg
 Inhalation LC50 (1h) Guinea pig > 633 ppm
 Dermal LD50 Rabbit > 2000 mg/kg
 Oral LD50 Rat > 5000 mg/kg
 Inhalation LC50 (4h) Rat > 73.5 MG/L
 Dermal LD50 Rabbit > 12800 mg/kg
 Oral LD50 Rat = 5000 mg/kg
 Inhalation LC50 (4h) Rat > 40 MG/L
 Dermal LD50 Rabbit = 15433 mg/kg
 No data available
 Inhalation LC50 Mouse = 6.2 MG/L
 Dermal LD50 Rabbit = 5 g/kg
 Oral LD50 Rat > 5 g/kg
 No data available

12. ECOLOGICAL INFORMATION

Ecological Toxicity: Severe ecological hazard. This product may be toxic to plants and/or wildlife.
 Mobility: No data available This material (or one of its components), dissolves in water. If it enters the soil, it will be highly mobile and may contaminate ground water.

Ingredient	CAS #
Distillates (petroleum), hydrotreated light	64742-47-8
Petroleum hydrocarbon	1330-20-7
Glycol ether	112-34-5
Aliphatic hydrocarbons	142-82-5
Dimethyl carbinol	67-63-0
Petroleum hydrocarbon	100-41-4
Citrus distillates	5989-27-5

Toxicological Data

96HR LL50 Rainbow Trout 2 MG/L
 48HR EL50 Daphnia 1.4 MG/L
 72HR EL50 Algae 1 MG/L
 Aquatic LC50 (96h) MINNOW 24 - 30 MG/L
 Aquatic LC50 (24h) Daphnia 100 - 1000 MG/L
 Code:
 Aquatic LC50 (96h) Bl gill = 1300 MG/L
 Aquatic LC50 (24h) Daphnia = 2850 MG/L
 No data available
 Aquatic LC50 (24h) Fish = 4 MG/L
 48HR EC50 Daphnia = 1.5 MG/L
 96HR EC50 Algae = 3.7 MG/L
 No data available
 Aquatic LC50 (96h) MINNOW = 9640 MG/L
 24HR EC50 Daphnia > 10000 MG/L
 No data available
 Aquatic LC50 (96h) Rainbow Trout = 8.4 MG/L
 48HR EC50 Daphnia = 9.55 MG/L
 72HR EC50 Algae 4.9 MG/L
 Aquatic LC50 (96h) MINNOW 1 - 1 MG/L
 48HR EC50 Daphnia = 70 MG/L
 No data available

13. DISPOSAL CONSIDERATIONS

Disposal : Dispose according to Federal, State and local regulations.

14. TRANSPORTATION INFORMATION

Agency	UN Number	Proper Shipping name	Hazard Class	Packing Group
DOT	UN1950	Aerosols, Flammable†	2.1	Not applicable
IATA	ID8000	Consumer Commodity†	9	Not applicable
IMDG	UN1950	Aerosols, Flammable†	2.1	Not applicable

† "Limited Quantities" may be applicable for this transportation mode.

15. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

COMPONENT	CAS #	% BY WEIGHT	Regulatory Body
Xylene	1330-20-7	7 - 13	SARA Section 313
Ethyl benzene	100-41-4	1-5	SARA Section 313
		1 - 5	

All components of this product are listed on the TSCA inventory.



WARNING: This product can expose you to Cumene, Ethyl benzene, which is(are) known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

16. OTHER INFORMATION

Other Information : SDS Prepared by L. Dean Swartz, SDS Coordinator

Version Date: 07/27/21

This information contained in this SDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.