Stoner B580 Express Wax

Revision Date: 8/19/2018

Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

Section 1. Product and Company Identification

Product Identifier B580 - Express Wax

Product Use Description: Violet opaque Lotion with fruity odor for use as an automobile paint protectant and gloss enhancer

Manufacturer or suppliers' details

Stoner Incorporated	Emergency Number (CHEMTREC):	800-424-9300
1070 Robert Fulton Hwy.	Customer Service:	800-227-5538
Quarryville PA 17566	Business Fax:	717-786-9088

Section 2. Hazards Identification

GHS Classification

Flammable Liquids : Category 3

Aspiration Hazard : Category 1

Eye Irritation : Category 3

GHS Label Elements

Hazard pictograms



Hazard Word

Danger

Hazard Statements

Flammable liquid and vapour May be fatal if swallowed and enters airways Causes mild skin irritation

Precautionary Statements

Take precautionary measures against static discharge Wear protective gloves/protective clothing/eye protection/face protection IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting In case of fire: Use dry sand, dry chemical or alcohol resistant foam for extinction Store in a well ventilated place. Keep cool Dispose of contents/container to an approved waste disposal plant.

3. Composition Information on Ingredients

CAS Number	Wt %	Component Name
64742-16-6	5-15%	Alkanes, C9-C11-iso
68551-19-9	5-15%	Alkanes, C12-C14-iso

Amounts specified are typical and do not represent a specification. Remaining components are proprietary, non-hazardous, and/or present at amounts below reportable limits.

4. First Aid Measures

EYE CONTACT

If splashed into the eyes, flush with clear water for 15 minutes or until irritation subsides. If irritation persists, call a physician.

SKIN

In case of skin contact, remove any contaminated clothing and wash skin with soap and water. Launder or dry-clean clothing before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

INHALATION

If overcome by vapor, remove from exposure and call a physician immediately. If breathing is irregular or has stopped, start resuscitation, administer oxygen, if available.

INGESTION

If ingested, DO NOT induce vomiting; call a physician immediately.

5. Fire Fighting Measures

EXTINGUISHING MEDIA AND FIRE FIGHTING PROCEDURES

Foam, water spray (fog), dry chemical, carbon dioxide and vaporizing liquid type extinguishing agents may all be suitable for extinguishing fires involving this type of product, depending on size or potential size of fire and circumstances related to the situation. Plan fire protection and response strategy through consultation with local fire protection authorities or appropriate specialists.

Use dry chemical, foam or carbon dioxide to extinguish the fire. "Water may be ineffective", but water should be used to keep fire-exposed containers cool. If a leak or spill has ignited, use water spray to disperse the vapors and to protect persons attempting to stop a leak. Water spray may be used to flush spills away from exposures. Minimize breathing of gases, vapor, fumes or decomposition products. Use supplied-air breathing equipment for enclosed or confined spaces or as otherwise needed.

DECOMPOSITION PRODUCTS UNDER FIRE CONDITIONS

Fumes, smoke, carbon monoxide, sulfur oxides, aldehydes and other decomposition products, in the case of incomplete combustion.

6. Accidental Release Measures

CLEAN WATER ACT / OIL POLLUTION ACT

This product may be classified as an oil under Section 311 of the Clean Water Act, and under the Oil Pollution Act. Discharges or spills into or leading to surface waters that cause a sheen must be reported to the National Response Center (1-800-424-8802).

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Shut off and eliminate all ignition sources. Keep people away. Recover free product. Add sand, earth or other suitable absorbent to spill area. Minimize breathing vapors. Minimize skin contact. Ventilate confined spaces. Open all windows and doors. Keep product out of sewers and watercourses by diking or impounding. Advise authorities if product has entered or may enter sewers, watercourses, or extensive land areas.

Assure conformity with applicable governmental regulations. Continue to observe precautions for volatile, combustible vapors from absorbed material.

7. Handling and Storage

HANDLING PRECAUTIONS

This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode.

Keep product away from ignition sources, such as heat, sparks, pilot lights, static electricity, and open flames.

8. Exposure Controls and Personal Protection

64742-16-6	Alkanes, C9-C11-iso

68551-19-9 Alkanes, C12-C14-iso

500 PPM, 2000 MG.M3, TWA OSHA Z-1 1200 MG/M3, TWA, Manufacturer explosive concentrations of vapor in air. No smoking, or use of flame or other ignition sources.

RESPIRATORY PROTECTION

Use supplied-air respiratory protection in confined or enclosed spaces, if needed.

PROTECTIVE GLOVES

Use chemical-resistant gloves, if needed, to avoid prolonged or repeated skin contact.

EYE PROTECTION

Use splash goggles or face shield when eye contact may occur.

OTHER PROTECTIVE EQUIPMENT

Use chemical-resistant apron or other impervious clothing, if needed, to avoid contaminating regular clothing, which could result in prolonged or repeated skin contact.

WORK PRACTICES / ENGINEERING CONTROLS

To prevent fire or explosion risk from static accumulation and discharge, effectively bond and/or ground product transfer system in accordance with (THE) National Fire Protection Association PUBLICATIONS.

9. Physical and Chemical Properties

Flash Point 39.4	4°C (102.9°F) TCC	Upper Flamability L	imit No Data Available
Auto Ignition 336	^{э°} С (637°F)	Lower Flamability I	imit No Data Available
Physical State Li	quid	Color Violet	Vapor Press 6.8 mmHg
pH 6.5	Specific Gravity .98	3	Viscosity 40 cst
Vapor Density (A	ir=1) 4.5	Melting Point °F 32	Odor Floral
Water Solubility 10. Stability and	Slightly dispersable Reactivity	VOC Content	1.3 lb/Gallon (see section 15)

Stability Stable Hazardous Polymerization Not Expected to Occur

Conditions to Avoid Keep away from extreme heat, Strong Acids, Alkalies and Oxidizers such as Chlorine, other Halogens, Hydrogen Peroxide and Oxygen

Hazardous No substances are readily identifiable from composition but no degradation data is available.

11. Toxicological Information

NATURE OF HAZARD AND TOXICITY INFORMATION Prolonged or repeated skin contact with this product tends to remove skin oils, possibly leading to irritation and dermatitis; however, based on human experience and available toxicological data, this product is judged to be neither a "corrosive" nor an "irritant" by OSHA criteria.

This product is judged to have an acute oral LD50 (rat) greater than 5 g/kg of body weight, and an acute dermal LD50 (rabbit) greater than 3.16 g/kg of body weight.

12. Ecological Information

Do not discharge this product into public waters or waterways unless authorized by a National Pollution Discharge Elimination System (NPDES) permit issued by the Environmental Protection Agency (EPA). Toxicity to fish

Alkanes, C9-11-iso : LC50: 1,000 mg/l Exposure time: 96 HR Species: Oncorhynchus mykiss (rainbow trout) see user defined free text

Toxicity to daphnia and other aquatic invertebrates.

Alkanes, C9-11-iso : LC50: 1,000 mg/l Exposure time: 48 HR Species: Daphnia magna (Water flea) see user defined free text

13. Disposal Considerations

Options for disposal of this product may depend on the conditions under which it was used. To determine the proper method of disposal, refer to RCRA (40 CFR 261), as well as federal EPA and state and local regulations.

Please refer to Sections 5, 6 and 15 for additional information.

14. Transportation Information

Domestic Transportation, not by air:

Not regulated

Transported by marine vessel:

UN1993, Flammable Liquid n.o.s. (Naphtha Solvent), 3, PGIII, Limited Quantity

Transportation by Air IATA:

UN1993, Flammable Liquid n.o.s. (Naphtha Solvent), 3, PGIII

15. Regulatory Information

EPCRA - Emergency Planning and Community Right-to-Know CERCLA Reportable Quantity : Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity: This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards: Fire Hazard

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65 This product contains no California Proposition 65 ingredients that cause cancer, birth defects or other reproductive harm.

All components of this product are listed on the U.S. TSCA inventory.

CARB VOC info: 14.9% VOC as regulated by CARB Consumer Products requirements, LVP-VOC

exception ARB VOC Info: 1.3 lb/gal VOC; 155.8 g/L

16. Other Information Revision Date 10/19/2015

The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.

Key or legend to abbreviations and acronyms used in the safety data sheet ACGIH American Conference of Government Industrial Hygienists LD50 Lethal Dose 50% AICS Australia, Inventory of Chemical Substances LOAEL Lowest Observed Adverse Effect Level DSL Canada, Domestic Sub- stances List NFPA National Fire Protection Agency NDSL Canada, Non-Domestic Sub- stances List NIOSH National Institute for Occupational Safety & Health **CNS** Central Nervous System NTP National Toxicology Program CAS Chemical Abstract Service NZIoC New Zealand Inventory of Chemicals EC50 Effective Concentration NOAEL No Observable Adverse Effect Level EC50 Effective Concentration 50% NOEC No Observed Effect Concentration EGEST EOSCA Generic Exposure Scenario Tool OSHA Occupational Safety & Health Administration EOSCA European Oilfield Specialty Chemicals Association PEL Permissible Exposure Limit EINECS European Inventory of Exist- ing Chemical Substances PICCS Philipines Inventory of Commercial Chemical Substances MAK Germany Maximum Concentration Values PRNT Presumed Not Toxic GHS Globally Harmonized System RCRA Resource Conservation Recovery Act >= Greater Than or Equal To STEL Short-term Exposure Limit IC50 Inhibition Concentration 50% SARA Superfund Amendments and Reauthorization Act. IARC International Agency for Re- search on Cancer TLV Threshold Limit Value

IECSC Inventory of Existing Chemical Substances in China

TWA Time Weighted Average

ENCS Japan, Inventory of Existing and New Chemical Sub- stances

TSCA Toxic Substance Control Act

KECI Korea, Existing Chemical Inventory

UVCB Unknown or Variable Composition, Complex Reaction Products, and Biological Materials

<= Less Than or Equal To

WHMIS Workplace Hazardous Materials In- formation System

LC50 Lethal Concentration 50%