

Your excellent helper in cable test!

# Wall Pipe Blockage Detector User Manual



Your excellent helper in cable test!





# Please read the safety precautions before using or repairing this equipment.

- After use, please turn off the power supply
- Because the device uses electromagnetic for detection, there may be noise interference when it is close to the electric wire, electronic devices or electric radiation
- When detecting metal pipes, the detection distance will be reduced due to electromagnetic shielding(the detection distance of 3mm thick iron pipe is about 15-20cm)
- If the blockage is found, please take back the detecting cable before digging
- Please use standard 5V power adapter and micro\_ USB cable to charges the instrument.
- If it is not used for a long time, please keep it after full charge. It is recommended to charge the battery once every half a year to protect the instrument battery and prolong the service life.

# **Table of Contents**


Overview	0
1. Main function & features	02
2. Specifications	03
3. Product usage	04
4. Probe replacing method	06
5. Packing list	09
6. Usage scenarios	09
7. Simple fault description	10
8. Sketch of Noyafa series products	11

### Overview

The instrument can be used in all kinds of scenarios, caused by various reasons of iron pipe, PVC pipe,

Plastic pipe, cement pipe, steel pipe, copper pipe and other metal and non-metal pipe blockage.Can be

Quick and accurate positioning of the plugging point of the pipeline buried in the cement wall. floor and land.



1	OFF/ON	2	Charging port
3	Charging port	4	Headphone jack
5	Sensitivity adjustment	6	Power light
7	Signal light *5 charging port	8	Horn hole

#### 1. Functional features

#### 1.1The emitter

- Probe Self Checking:
- Open/ Short circuit Open circuit: Twice "Di" for fault notice Normal; Single long beep "Di",the probe enters the working mode. Charging indicator function: red light when charging, green light when full.
- Low power alarm and battery protection function: low voltage (lt;3.6V), green light flashing alarm, ultra-low pressure (<3.4V), the instrument a utomatically shuts down to protect the battery.
- Automatic shutdown function, automatic shutdown after 1 hour, to prevent forgetting to shut down resulting in power depletion

#### 1.2Receiver

 Power detection function: automatically detect the battery power turning on, represented by 5 LED lights, all on means full power





# • Charging indicator function:

the red light is always on during charging; Full, always green



#### Power alert function:

Normal power: green light is always on and low voltage (<3.6V), green light 1 second slow flashing alarm, ultra-low pressure (&lt;3.2V), the green light flashes for 3 seconds and then turns off to protect the battery

#### • Automatic shutdown function:

Utomatic shutdown after 30 minutes, to prevent forgetting toshut down resulting in power depletion.

### • Indicating function of signal intensity:

The signal lamp can accurately indicate the signal intensity, and has the function of brightness adjustment

• The detection range is adjustable from 5 cm to 50cm

# 2. Specifications

	Model	NF-5120	NF-5130	NF-5140
	Tube Lamp	20M	30M	40M
	Applications	y 18650 Lithium battery 2600mAh 300Hz		
	Power supply			
Emitter	Working frequency			
	Working Hour			
	Working temperature			
	Size			
	Weight	1500g		

	Sensitivity adjustment	Yes
	Distance range	Non-pipe pipe:0~40cm, metal-pipe: 0~ 15cm
	Power supply	Lithium1400mAh
	Working frequency	300Hz
Receiver	Working Hour	5H
	Working Temperature	10~40°C
	Size	65x360x40mm
	Storage Temperature	-10°C~50°C
	Voice Indication	Yes

# 3. How to use the product

#### 3.1. Turn on and off the transmitter:

- Press the power button for 2 seconds in the off state, when the power indicator is green, otherwise it will be turned off
- Receiver: turn the knob clockwise to power on the battery in thefirst 2 seconds after power on, using 5 LED to represent the battery, all of which are fully charged


## 3.2Pre-use inspection.

- Transmitter: turn on and spin the probe out for a while, and the probe is at a distance from the transmitter.
- Receiver: power on to the maximum sensitivity, put the receiver close to the transmitter probe, if the receiver emits a strong signal sound, it means that the instrument is normal, such as the receiver does not make sound or the sound is very low, the probe needs to be replaced.

#### 3.3Start detection (figure 3-1)

- Transmitter: put the transmitter probe into the pipe, turn the transmitter turntable handle line into the pipe, until the emitter pipeline feels the resistance and cannot go further into the pipeline, then the position of the transmitter probe is the blocking position.
- Receiver: adjust the receiver sensitivity to the maximum, move the receiver transmitter probe closer along the pipe, the stronger the signal received, the more signal strength indicator lights up, the louder the tone.
- •The strongest signal is the blocking point. In some usage scenarios, there may be ambient noise, so that the sound emitted by the receiver cannot be heard clearly and headphones can be used to work.

Tips: use high sensitivity, quickly locate the approximate position of the plugging point, and then adjust the sensitivity to locate the plugging point accurately.



(figure 3-1)

## 3.4Outgoing / unwinding method





- 1. Correct exit / take-up: turn the wheel clockwise / counterclockwisewith the right hand after lifting the instrument with the left hand.
- 2.Wrong take-out / take-up: lifting the instrument with the left handand pulling the wire out with the right hand and pushing the wire in will cause the pipeline to get tuck or even break

# 4. Probe replacement method



1.Remove the parts to replace the probe

1	502 glue	2	Large heat shrinkable tube
3	Protective sleeve	4	Thin copper tube
5	Probe	6	-


2.Use the tool to subtract the damaged probe part of thesignal receiver



3. Peel off the 5mm of the signal wire (remove the rubber from the fiber core).



4.Connect the wire core with tiny cooper tube by clampping the bottom part of the tube



5.Insert the probe and clamp the thin copper tube with pliers and put the heat shrinkable tube



6.Put on the protective cover and drop 502 glue



7.Put on a large heat shrinkablepipe lighter



8. Complete probe replacement



Your excellent helper in cable test!

# 5. Packing list

1	Transmitter (lithium battery)	1ps
2	Receiver (lithium battery)	1ps
3	Recharging Cable	1 piece
4	Earphone	1 pair
5	Transmitter Probe Accessories	6sets
6	502 glue	1 branch
7	operating instruction	1 piece
8	Certificate / Warranty Card	1 piece

# 6.Product usage scenarios



# 7. Simple fault description

Fault phenomenon	Possible causes of failure	Suggested solutions
Machine can not turn on (the light is not on after boot)	Receiver battery poor contact	Please check number battery interface
	Low battery power	Please charge and test again
Receiver silence or shorter detection distance	The receiver is sensitive and low	Please adjust the sensitivity and test again
	The receiver is too far from the transmitte	Please approach the launcher for further testing
	Launcher not activated	Check the transmitter for boot
	Transmitter probe damaged	Replace probe
Non-signal noise from receiver	Strong electromagnetic interference nearby	Test to empty areas of useless appliances
	The charger may cause electromagnetic interference to the machine	Do not use the machine while charging
Non-signal noise from receiver	Poor contact with charging interface	Please check the charging line is in good contact
	Damage to charging line	Please change the line and test again
	Receiver battery contact poor	Please plug in the battery interface
Power indicator flashing	Low battery power	Please charge and test again
If the above-mention	ned failure occurs, or above so	lution is invalid please

If the above-mentioned failure occurs, or above solution is invalid, please contact the customer to resolve it

# 8. NOYAFA series product sketch



NF-8601S



NF-309



NF-198



NF-511



NF-2030



NF-488



NF-858C



NF-911



NF-707



NF-711F



NF-521



NF-271

品号	品名		NF-5120&5130&5140说明书英文中性-V3		
版本	V3	日期	2023.07.18	产品名称	智能管道测堵仪
设计	HZL	公差(mm)		标品/订制品	标品
校对		审核		印刷颜色	彩色印刷
样品		类型	骑马钉	尺寸	210*145mm
材质工艺 128g铜版纸					
	V3较V2版本,更新探头自检描述、接换新探头描述				
变更记录					