

Urban Planter User Assembly Instructions

Read these instructions and general information to properly and safely assemble the urban planter.

5602-000200-00-00, 30"x10" planter

30" x 10" URBAN PLANTER BODY - 1 pc

SINGLE LEG-BLK - 2 pcs

3/8"-16 HEX COUPLING NUT ZINC -1 pc

3/8"-16 x 4.5" HEX HEAD BOLT-ZP - 1pc

3/8" FLAT WASHER - 2 pcs

5603-000200-00-00, 36"x15" planter

36" x 15" URBAN PLANTER BODY - 1 pc

SINGLE LEG-BLK - 2 pcs

3/8"-16 HEX COUPLING NUT ZINC - 1 pc

3/8"-16 X 5.5" HEX HEAD BOLT-ZP - 2 pcs

3/8" FLAT WASHER-ZP - 2pcs



1. With the planter upside down, place the first leg on the planter. secured under the mounting lip,

Ensure the leg is pushed down and and repeat for 2nd leg.



4. Screw on the connector nut between the 2 bolts.

CHECK CONTENTS MATCH ABOVE

Tools required (NOT Supplied): One ratchet with 9/16" socket One 9/16" wrench



2. Place a washer on each bolt and slide bolt into opening of leg as shown above.



3. Repeat step 2 with other leg.



5. Using a 9/16" wrench and ratchet, tighten the first bolt as show, ensure not to over tighten the bolts.



6. Repeat step 5 on 2nd bolt, assembly should now be rigid and secure.



9. Completed assembly. Fill the planter with soil and plants.