

## Xtreme Charge® Battery Charger

Battery Maintenance Charger for ALL vehicles

Part #: 200X010

Model #: XC400

Replaces the XC-100

Batteries last up to  
**3X**  
LONGER!

- Charges and maintains ANY 12-volt lead-acid battery
- Extends battery life with desulfating pulses up to 3x longer

What makes PulseTech different?

- Pulse conditioning, provided by PulseTech Products, minimizes lead sulfate crystals on the battery plates, enhancing the performance and extending the life cycles of any size or type of 12V lead-acid battery

- Minimizing the lead sulfate crystals allows the battery to accept more power
- PULSE technology is NOT “Pulse Charging” but a high-frequency conditioning pulse on one circuit and a proprietary charging algorithm on the other

This innovative, state-of-the-art battery charger automatically knows what to do so you don't have to be a battery expert to use it. Unlike other smart chargers on the market, you don't need to select the battery type or the proper charge rate for your car's battery to avoid the risk of unsafe or improper charging.

There's no guess work because the fuse-protected, spark-proof Xtreme Charge works on any type of 12-Volt lead-acid battery - VRLA, AGM, gel and flooded. Proprietary algorithms combined with microprocessor controlled technology measure the battery's voltage and current to automatically determine and deliver the precise charge rate throughout the five-stage charge process.

What is Pulse Technology?

The Xtreme Charge goes beyond standard charging and maintenance. It employs PulseTech's exclusive patented Pulse Technology that emits optimized frequency pulses throughout the charging process. This technology is designed to minimize and reduce the buildup of lead sulfate crystals on the battery's plates - the main cause of battery failure. By effectively reducing lead sulfate deposits, your battery will charge deeper, maintain greater reserve capacity and last up to three times longer.

The quick disconnect feature allows you to permanently attach lugs to the battery and easily switch between lugs and clamps. The status light column shows you when the unit power is on, pulsing and charging. The battery light column indicates the percentage of the battery's state of charge - 25%, 50%, 75% or 100%.



### Specifications:

Input Voltage	100-250 V ac
Max Charge Current	4 amps
Power Cord Length	6 ft
Main Battery Cable Length	6 ft
Lug/Clamp Cable Length	2 ft
Fuse Protected Cables	
Quick Disconnect at Battery	

