

24VPSC-10W, 24-Volt Battery Pulse Solar Charger Desulfator, 10W

Part #: 735X690

Model: 24VPSC-10W

NSN: pending

Description:

Rated at 357mA this 10-Watt Pulse Solar Charger provides high frequency pulsing across two, four or six batteries wired in series parallel. It works with any lead-acid batteries (VRLA, AGM, flooded cell and gel) and keeps batteries in like-new condition all the time no matter how long vehicles or equipment sit unused outside.

This unit utilizes our unrivaled solar charging system combined with our patented high frequency pulsing circuit, Pulse Technology, to ensure batteries start when needed. Pulse Technology reverses the naturally occurring process of battery sulfation - the main cause of battery failure. This allows batteries to accept, store and release maximum power all the time extending battery life.

Safe, reliable and weatherproof, this unit prevents dead batteries by keeping them in like-new condition indefinitely. A LED light indicates the circuit is energized and the unit is working.

Specifications:

Input Electrical	Solar powered
Output Electrical	357 mA
Output Voltage	33 VOC
Circuit Box Dimensions	4.9" x 1.8" x 1"
Solar Panel Dimensions	9.8" x 12.7" x 0.125"
LED	Indicate circuit is energized and unit is working
Box to Clip Wire Length	50"
Box to Panel Wire Length	25"
Shipping Weight	2.6 lbs

