

24VPSC-25W NATO, 24V Battery Solar Pulse Charger Desulfator, 25W w/NATO

Part #: 735X712

Model: 24VPSC-25W NATO

NSN: pending

Description:

Rated at 0.833 Amps, this 25-Watt Pulse Solar Charger charges and desulfates all 24-Volt battery systems (including VRLA, AGM, gel and flooded cell) on vehicles or equipment stored outside. No AC power is needed as the sun's energy is harnessed to prevent the normal loss of battery power on stored vehicles, generators and heavy equipment no matter how long they sit unused.

This unit utilizes our unrivaled solar charging system combined with our patented high frequency pulsing circuit, Pulse Technology, to ensure batteries start when needed no matter how long vehicles or equipment sit unused outside. Pulse Technology reverses the naturally occurring process of battery sulfation - the main cause of battery failure. This allows batteries to accept, store and release maximum power all the time extending battery life.

Safe, reliable and weatherproof, this unit prevents dead batteries by keeping them in like-new condition indefinitely. A LED light indicates the circuit is energized and the unit is working. A special external heavy duty plug connects directly to vehicles, generators and support equipment.



Specifications:

Input Electrical	Solar Powered
Output Electrical	833 mA
Output Voltage	33 VOC
Circuit Box Dimensions	4.9" x 1.8" x 1"
Solar Panel Dimensions	14.4" x 17.9" x 0.125"
LED	Indicates circuit is energized and unit is working
Box to NATO Plug Wire Length	50"
Box to Panel Wire Length	25'
Shipping Weight	4.2 lbs