

**HD PC-12 Pallet Charger** 

Part #: 746X820 Model #: HD PC-12

NSN: 6130-01-532-7711

## **Description:**

The Pallet Charger is a 12V, 6 amps per channel, 12-station charging unit that uses universal electrical input. The charger can be connected to any type or size of 12V lead acid battery (VRLA, AGM, gel and flooded cell). Each of the 12 charge stations operate in isolation from one another, allowing any combination of batteries to be recharged at the same time.

There's no need to move the batteries, simply roll the Pallet Charger to wherever the batteries are located. The HD Pallet Charger senses the condition of each individual battery and provides the appropriate charge without the risk of overheating or overcharging the battery.

Pulse Technology removes and prevents the buildup of sulfate crystals on the battery plates. This allows batteries to charge deeper, maintain greater reserve capacity and last up to 3 times longer. With one-switch control and progressive, easy-tounderstand LED information display, operator training requirements are minimized. LEDs show battery

disconnected, bad battery, recovery charge, pulse charge and charge complete.



## **Specifications:**

Input Electrical	100-250 V AC, 7.5-15A, 50/60 Hz
Output Electrical	14.8V, 72A; 12 Channels
Max Charging	14.8V @ 6A per Channel
Enclosure	Sand steel cabinet on solid rubber wheels
<b>Enclosure Dimensions</b>	17.5" x 28" x 14"
Operating Temperatures	0°F - 130°F (-18°C - 54°C)
Leads	8' - 14 AWG
Termination	Battery clamps
Weight	98 lbs with leads
Mounting	Mobile unit

