



# MODEL T29/T29A

# **SOFT SERVE FREEZER**

TWIN TWIST, COUNTERTOP, DIGITAL CONTROL



Ideal for medium capacity outlets to add soft serve ice cream and frozen yogurt. innovative design keeps operation simple and helps reduce cost of ownership.



#### **FAST FREEZE DOWN**

Patented high efficiency heat exchanger allows fast freeze down with low energy consumption



### **DIGITAL CONTROL AND DISPLAY**

Digital control provides access to system settings and displays critical system information



#### LOW MIX INDICATOR

Light turns "ON" at low mix to alert operator to add mix  $\,$ 



#### SELF CLOSING DISPENSING VALVE

Automatically prevents product overflow after dispense



#### **DISPENSE SPEED CONTROL**

Provides flexibility in dispense rate control for different applications



#### **HOPPER AGITATORS**

Maintain product consistency and prevent product separation



#### **AUTO PROGRAMMING**

Allows automatic switching of operation modes based on preset schedules



# STANDBY

Maintains product temperature in both mix hopper and freezing cylinder below 4.4°C (40°F) overnight



## **SAFETY PROTECTIONS**

- Low temperature and motor overload shut-off to protect in the event of cylinder freeze up
- High pressure switch to prevent compressor overheating
- Thermal overload to protect from motor overheating

SIMPLE BUT POWERFUL CLASSY DESIGN THAT OFFERS
OUALITY AND EASE OF USE


**MAXIMISE YOUR PROFITS** 






# MODEL T29/T29A

# SOFT SERVE FREEZER MACHINE





















#### **SPECIFICATIONS**

WEIGHT

Net

| Flavours                   | 2 + Twist        |
|----------------------------|------------------|
| Freezing Cylinders         | 2 x 1.7L         |
| Mix Hoppers                | 2 x 12L          |
| Output Capacity (80 grams) | 300 serves/hr    |
| Clearance Requirements     | 152mm/6" on left |
|                            |                  |

KG/LB (Gravity)

155 / 344

KG/LB (Pump)

165 / 367

| Shipping   | 170/ 378       | 180 / 400        |
|------------|----------------|------------------|
| Volume     | 0.57 CBM / 1 S | ).97 CBF         |
| DIMENSIONS | NET (MM/IN)    | SHIPPING (MM/IN) |
| Width      | 552 / 21.7     | 620 / 24.4       |
| Depth      | 652 / 25.7     | 800 / 31.5       |
| Height     | 955 / 37.6     | 1140 / 44.9      |

| ELECTRICAL   | AMP | VOLTS | POWER(KW) |
|--------------|-----|-------|-----------|
| 220-240/50/1 | 16  | NA    | NA        |
| 208-230/60/1 | 16  | NA    | NA        |

### **FEATURES**

| CONTROL SYSTEMS                  | SINGLE DIGITAL |
|----------------------------------|----------------|
| REFRIGERATED HOPPERS             | $\checkmark$   |
| HOPPER AGITATOR AVAILABLE        | $\checkmark$   |
| TEMPERATURE DISPLAY              | V              |
| STANDBY MODE                     | $\checkmark$   |
| AUTO CLOSING DISPENSING VALVES   | <u> </u>       |
| DISPENSING SPEED CONTROL         | $\checkmark$   |
| LOW MIX INDICATOR LIGHT          | $\checkmark$   |
| LOW MIX INDICATOR ALARM          | $\checkmark$   |
| LOW TEMPERATURE PROTECTION       | $\checkmark$   |
| MOTOR AMPERAGE PROTECTION        | <b>✓</b>       |
| HIGH PRESSURE PROTECTION         | V              |
| THERMAL OVERLOAD PROTECTION      | V              |
| T29A: AIR PUMP VERSION AVAILABLE | $\checkmark$   |