

Talkpod

TMC04

Universal Rapid Six-Unit Charger

Easy and Fast to Charge!



The durable Talkpod Batteries Chargers through the verification of the global market, superior quality, reliable performance; you can ensure that the performance of the two-way radio performance and efficiency. Batteries can be safely left on the TMC04 six-unit charger without damaging the battery and batteries are kept fully charged, so you can be assured they are always ready when you head for a call.

- Tri-chemistry, AC or DC input; Smallest & Lightest (Only 800g); Tough poly carbon casing; LED charging/charged indicator; One year warranty;
- Charge six different batteries with or without radio attached;
- Space saving design with dual power source allows you to charge your radios anywhere.
- The TMC04 is a rapid rate, tri-chemistry multi-unit tough poly carbon casing;
- With a self switching wall cube power supply. The TMC04 utilizes the same interchangeable cup system as all Talkpod chargers;

A composite image. The background shows a factory worker in a dark uniform and safety glasses, working with a large, glowing orange metal piece. The foreground is a blue gradient area. On the left, a white lightning bolt icon is above the text 'EASY AND FAST TO CHARGE!'. On the right, the Talkpod logo is above the text 'MULTIPLE BATTERY CHARGER' and 'TMC04'. A small image of the TMC04 charger is also visible in the bottom left of the blue area.

General Specifications	
Model Number	TMC04
Input Voltage	110–220V
Charge Battery Chemistry Type	Li-Ion, Ni-MH, Ni-Cd
Voltage of Li-Ion Charged	2xCells 8.3V/1xCell 4.2V
Voltage of Ni-Cd & Ni-NH Charged	6xCells 8.6V
Charging Current	500–1000mA
Color Options	Black housing
Charging Indicators	Green, Red
Format	2x3

Power Supply	
Adapter Type	Switching Power Supply
Adapter Input	110–220V 50/60Hz
Adapter Output	13.2V 3A
Adapter Jack	2.5mm

General and Environmental	
Dimensions	495x108x65(mm)
Weight	800g
Operating Temperature	–10°C to 55°C
Storage Temperature	–40°C to 85°C
Operating Humidity	30%–90% RH
Stream Hours	72 hours
Patent	All plastic housing design
Warranty	1 Year

Specifications subject to change without notice.