

Havis Docking Station

Fully Rugged Z710 & ZX70

DS-GTC-710

Getac



Rugged Tablet Solution

- Low profile, lightweight and flexible design
- Port replication with integrated strain relieving
- Dual Pass-Thru Antenna Connections (Optional)
- External Power Supply (Optional)
- Bundles available for convenient solutions

PART NUMBER	ETHERNET	USB 2.0	USB 3.0	HDMI	VGA	SERIAL	POWERED SERIAL	DISPLAY PORT	SPEAKER/MIC	POWER INPUT	PASS-THRU ANT	ANT TYPE	EXT POWER	INT POWER
DS-GTC-711**	1	2 Rear		1		1			Speaker	12 V*				
DS-GTC-711-2**	1	2 Rear		1		1			Speaker	12 V*	Dual	SMA		
DS-GTC-712**	1	2 Rear		1		1			Speaker	12 V			LPS-164	
DS-GTC-712-2**	1	2 Rear		1		1			Speaker	12 V	Dual	SMA	LPS-164	
DS-GTC-714***	1	2 Rear		1		1			Speaker	12 V*				
DS-GTC-714-2***	1	2 Rear		1		1			Speaker	12 V*	Dual	SMA		
DS-GTC-715***										12 V*				
DS-GTC-715-2***										12 V*	Dual	SMA		
DS-GTC-716													LPS-164	
DS-GTC-716-2											Dual	SMA	LPS-164	
DS-GTC-717***	1	2 Rear		1		1			Speaker	12 V			LPS-164	
DS-GTC-717-2***	1	2 Rear		1		1			Speaker	12 V	Dual	SMA	LPS-164	
DS-GTC-718***										12 V			LPS-164	
DS-GTC-718-2***										12 V	Dual	SMA	LPS-164	

* Requires an external Getac authorized DC power supply

** JAE Docking Connector

*** POGO Docking Connector

SPECIFICATIONS

Height: 8.7-in (22.1 cm)
 Width: 9.2-in (23.4 cm)
 Depth: 2.9-in (7.4 cm)
 Weight: 1.5 lbs (0.7 kg)
 Mounting: VESA 75

CERTIFICATIONS & TESTING

CE Certified; RoHS Compliant
 Vibration Testing: MIL-STD 810G 514.5
 Impact Test: Crash Simulation per SAE J1455
 Cycle Test: Latch Tested 30,000 cycles
 Environmental Testing: Hot/Cold Operation & Storage