AMP-Q37 EU 16A / AMP-Q74 RED 32A / AMP-Q11 RED 16A / AMP-Q22 RED 32A

Certifications: CE, EMC, LVD, FCC, RoHS, UKCA

Functions: charging scheduling(charging delay possibility), charging limit change, charging statistics, charging history, mobile app integration Android/Tuya, Tuya integration

Set includes: charger, charger holder, cable plug holder, transport bag.

Charger parameters:

	3.7kW	**7.4kW**	**11KW**	**22KW**
Connector Type	Schuko	Red CEE 32A	Red CEE 32A	Red CEE 32A
Output Power	3,7	7,4	11	22
Voltage	1x230V 16A	1x230V 32A	3x230V 16A	3x230V 32A
Frequency	50/60 Hz			
RCD	A + DC 6mA, CCID20	A + DC 6mA, CCID20	A + DC 6mA, CCID20	A + DC 6mA, CCID20
Protection	Input overvoltage,Low temperature discharge,Output short circuit,Anti-lightning strike,Charging overvoltage,Charging overcurrent,High temperaturecharging,Low temperature charging,Discharge undervoltage,-Discharge overcurrent,High temperature discharging	Input overvoltage,Low temperature discharge,Output short circuit,Anti-lightning strike,Charging overvoltage,Charging overcurrent,High temperaturecharging,Low temperature charging,Discharge undervoltage,-Discharge overcurrent,High temperature discharging	Input overvoltage,Low temperature discharge,Output short circuit,Anti-lightning strike,Charging overvoltage,Charging overcurrent,High temperaturecharging,Low temperature charging,Discharge undervoltage,-Discharge overcurrent,High temperature discharging	Input overvoltage,Low temperature discharge,Output short circuit,Anti-lightning strike,Charging overvoltage,Charging overcurrent,High temperaturecharging,Low temperature charging,Discharge undervoltage,-Discharge overcurrent,High temperature discharging
Dimensions (charger body only)	26.5*9.6*6.8cm	33.5*9.8*7cm	33.5*9.8*7cm	33.5*9.8*7cm
Dimensions box	41*21*19cm	41*21*19cm	47*25*21cm	47*25*21cm
Net weight	3.4KG	4.16KG	4.06KG	4.9KG
Weatherproof / Fall protection	IP66 / IK10	IP66 / IK10	IP66 / IK10	IP66 / IK10
Temperature operating	-30℃~+50℃	-30℃~+50℃	-30℃~+50℃	-30℃~+50℃
Temperature storing	-40℃~+80℃	-40℃~+80℃	-40℃~+80℃	-40℃~+80℃
Material	Aluminum + PC	Aluminum + PC	Aluminum + PC	Aluminum + PC
Color	Black/Dark Silver	Black/Dark Silver	Black/Dark Silver	Black/Dark Silver
Screen size	LED Indicator	2.8-inch	2.8-inch	2.8-inch
Cable	6m	5m	5m	5m
Cable parameters	3x2,5mm+1x0.5mm	3*6mm²+1*0.75mm²	5*2.5mm²+1*0.75mm²	5*6mm²+1*0.75mm²
Connectivity	Bluetooth / Wifi	Bluetooth / Wifi	Bluetooth / Wifi	Bluetooth / Wifi