

MAS MAYA

MAS MAYA BASE TECHNICAL DATA SHEET

DATE OF ISSUE: 4 NOVEMBER 2024

PRODUCT DESCRIPTION

Mas Maya Base is a versatile, flexible adhesive mortar specially formulated for smoothing and preparing surfaces for Mas Maya Coating. Ideal for creating a level and stable base, it provides strong adhesion to a variety of surfaces, ensuring optimal bonding and a flawless, crack-resistant finish for Mas Maya Coating applications.

Mas Maya Base is ideal for filling in cracks in surfaces, or imperfections - such as grout lines between tiles.

APPLICATION INSTRUCTIONS

1. Surface Preparation

- **Clean the Surface:** Ensure the surface is clean, dry, and free of dust, grease, or loose particles.

2. Mixing the Base

- **Mix Water and Base:** Add 1/3 liter of clean water for every kilogram of Mas Maya Base powder.
- **Mixing Process:** Stir the mixture by hand or with a mechanical drill until smooth and consistent, resembling yogurt. Allow the mixture to rest for 15 minutes, then give it a final stir.

3. Application Process

- **Trowel Application:** Use a steel trowel to fill in any gaps or cracks in the surface. The surface should be flat and smooth before applying Mas Maya Coating.
- **Drying Time:** Allow the Base layer to set for at least two hours before applying Mas Maya Coating.