

Warranty

- Warranty of this product commences from date of purchase and is non-transferrable
- 15 Years Full Warranty.
- If a problem is found with the product within the specified criteria within the warranty period, please contact Linsol directly, either by email info@linsol.com.au or phone (02) 4228 0481) and be ready to state the place of purchase, date of purchase and plumbers details including licence number, and your contact details. If you would like to make a claim in writing, address it to;

LINSOL PTY LTD
PO Box 88
Coniston, NSW 2500

"Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure".

In the event of a defect in workmanship or material within the warranty period, Linsol will bear the expense by either resupplying the product, supply an equivalent product if the original product is no longer available, repair the product, or reimburse the customer. This warranty is in addition to your other rights and remedies under the law in relation to the goods which this warranty relates to. This warranty will not cover any damage to the product due to misuse, negligence, improper installation, inadequate maintenance or other abuse or misuse.

For further queries please contact the place of purchase of this Linsol product.

www.linsol.com.au

© ALL INFORMATION IN THIS BOOKLET IS

HANDY HINTS FOR INSTALLATION AND MAINTENANCE

CLEANING

- A soft cloth is ideal for cleaning all chrome plated tapware.
 Never use an abrasive or harsh substance. Only use a mild liquid detergent to remove build-up and tough surface film.
- Regular cleaning with a soft cotton cloth will keep your tapware looking as good as the day you bought it.

INSTALLATION

- All tapware must be installed by a licensed plumber and must be installed to AS/NZS 3500 Series Standards
- Isolating stop valves must be installed with all applicable tapware.
- All new connections need to be flushed before installing any tapware to remove any shavings or impurities from the water lines.
- Linsol does not recommend dismantling the internal parts of any mixers as they have already been individually tested.
- If the incoming water pressure exceeds 1200kpa an approved pressure limiting valve must be used, and the tapware has not been tested for water pressure under 150kpa

Failure to comply with any of the above will void all warranties.