

UNIVERSAL QUICK DRYING PRIMER UNDERCOAT

Product Code 7000-6-56

PRODUCT INFORMATION

Typical Use

Quick Drying Primer Undercoat is a water-based, high opacity, dual purpose primer undercoat which is recoatable within 2 hours. It is suitable for use on interior woodwork and interior ferrous metals.

Pack Size 1.2.5 and 5 litre.

Colour Range White.

Composition (nominal)

Pigment: Non Lead Pigments.

Binder: Acrylic Copolymer.

Solvent: Water.

Volume Solids

36% (nominal).

Application Method

Brush, roller or spray.

Drying Times

Single coat at standard thickness:

Touch Dry: Dependent upon temperature and humidity.

Recoat: 2 hours.

Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 12 m²/litre.

SURFACE PREPARATION

Surfaces must be clean, dry, free from all defective or poorly adhering material, dirt, grease, wax etc.

Thoroughly rub down previously painted surfaces, using 'wet flattening' (wet & dry paper used wet) method where possible, then wipe off with a damp, lint free cloth.

Treat any knots in wood with an appropriate knotting solution.

Ferrous metals, remove any loose rust and mechanically abrade and degrease prior to painting

Wash brushes out with soap and water.

SYSTEM INFORMATION

Stir thoroughly before use.

New or bare surfaces:

2 coats of Quick Drying Wood Primer Undercoat.

Previously painted surfaces:

1 coat of Quick Drying Wood Primer Undercoat.

Allow to dry for a minimum of 2 hours between coats.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

WATER-BASED PAINT

Ensure good ventilation during application and drying.

Do not breathe spray. When spraying inside, wearing a cartridge mask of Assigned Protection Factor 10 x OEL for particulates is recommended.

Avoid contact with skin and eyes. When applying it is advisable to wear eye protection during spraying.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleanser. Do not use solvent, thinners or white spirit.

Keep out of the reach of children.

If swallowed, seek medical advice immediately and show this container or label.

Do not use or store by hanging on a hook.

Do not empty into drains or watercourses.

Safety data sheet available for professional user on request.

Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.

Special precautions should be taken during surface preparation of pre- 1960s paint surfaces over wood and metal as they may contain harmful lead.

This product contains max. 30g/l VOC – minimal VOC