FLIR SCION[®] OTM Outdoor Thermal Monocular



The FLIR Scion[®] OTM leverages high-performance thermal imaging and a refined user interface to quickly detect objects of interest and provide superior awareness in low visibility conditions. Built around the powerful FLIR Boson[®] core, the Scion OTM produces smooth thermal imaging up to 60 Hz and captures geotagged video and still images for playback long after the day is done. A rugged, IP67-rated housing and intuitive controls allow single-hand operation in harsh weather conditions, maintaining reliable thermal imaging in the most demanding outdoor environments.



ONBOARD VIDEO AND IMAGE RECORDING

Revisit every wildlife encounter in sharp thermal imaging.

The Scion OTM is ready to capture any wildlife encounter with onboard video and image recording. Smooth 60 Hz thermal imaging preserves details on moving objects while internal storage and a built-in microSD™ card slot provide enough memory for the most demanding trips. Additional Bluetooth[®] and Wi-Fi capabilities allow simple file transfer between devices.

VERSATILE LENS OPTIONS

Available long-range lenses for the Scion family of thermal monoculars offers a new level of clarity and reach.

High performance 18mm thermal lenses offer a choice between quick, close-proximity detection and finetuned, long-range observation. When your adventure demands reliable vision from a distance, premium Scion lenses can detect targets up to 1000 m away. 25 mm Scion optics leverage a manual focus ring to achieve a new level of clarity among FLIR thermal monoculars.

TRUSTED THERMAL DETECTION

Powered by the breakthrough FLIR Boson thermal core.

Able to perform at any time of day, thermal imaging pierces complete darkness, glaring light, and lingering haze to provide superior awareness in difficult conditions. The advanced image processing of FLIR's Boson thermal core paired with a 60 Hz image refresh rate provide smooth, unwavering vision in challenging environments.

TELEDYNE

SPECIFICATIONS

General	Scion OTM266	Scion OTM366	
Core Technology	BOSON 12 µm VO	BOSON 12 µm VOx Microbolometer	
Detector Resolution	640×512		
Refresh Rate	60 Hz		
Lens System	18 mm	25 mm	
Field of View (H × W)	$24^{\circ} \times 18^{\circ}$	$18^{\circ} \times 13^{\circ}$	
Optical Magnification	1x	1.3x	
Digital Zoom	1X 2X 4X 8X		
Internal Memory	2 GB Internal Storage / Optional microSD [™] Card (up to 128 GB)		
Focus	∞	Manual	
Eye Relief	16 mm		
Display	Quad-VGA (1280x960) High definition display		
Display Focus	Manual		
Features			
Color palettes	White Hot; Black Hot; Iron Bow; Rainbow; Graded Fire; Lava		
Viewing Modes	Scouting, Picture-in-Picture, Lock Span Mode		
GPS	Yes		
Advanced media capture	Ye	es	
Media capturing	2 GB Internal storage / Optional micro SD™card (up to 128 GB)		
Date/Time Stamp	Ye	es	
Auto Power OFF	Ye	es	
Magnetic Compass	Yes		
Accelerometer	Ye	es	
Interfacing			
USB Type	USB-C; Power In; Video Out; \	/ideo and Image File Transfer	
Power			
Battery Type / Life	6x CR123A 3V Lithium Batte o Rechargeable battery pac	r	

	Scion OTM266	Scion OTM366
Communications		
Bluetooth [™]	BLE 4.1+	
Wi-Fi	Video Streaming	
Physical		
Size	239 × 76.8 × 60.5 mm (9 × 3 × 2.4 in)	239×76.8×60.5 mm (9 × 3 × 2.4 in)
Weight	Unit only : 452g With Batteries (6): 565g	Unit only: 567g With Batteries (6): 680g
Environmental Rating	IP67 waterproof / 2m drop	
Operating Temperature	-20°c to 50°c	
Storage Temperature	-40°c to 70°c	
Color (Housing)	Green / Black	
Mounting	1/4-20 Tripod Mount / Optional docking station	
Country of Origin	USA	
Included in Box	SCION, Battery tray, 6xCR123, USB-C cable, Black MOLLE pouch, Quick Start Guide	

200 series units





DETECTION RANGE PERFORMANCE

18	mm

25 mm

Ranges calculated using Johnson criteria

Teledyne FLIR, LLC

9 Townsend West, Nashua, NH 03063 Phone: 1-888-959-2259 or (603) 321-7600 Fax: 1-888-959-2260

FLIR PRODUCT **REPAIR CENTER**

710 m 🐵

Support: https://flir.custhelp.com/ Register on: customer.flir.com

1000 m 💮

ORDER PLACEMENT, RETURN TO **STOCK AND INQUIRIES**

Email: OTS-Orders@flir.com

PRODUCT REGISTRATION

flir.com/support-center/support-hq/

TECHNICAL SUPPORT Email: OTS_support@flir.com This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited. For assistance with confirming the Jurisdiction & Classification of Teledyne FLIR, LLC products, please contact exportquestions@flir.com. ©2022 Teledyne FLIR, LLC. All rights reserved.

Revised on 02/25/22 OTS_SCION-OTM-60HZ-DS_update_22-0215



For more information contact: Sales@TeledyneFLIR.com

www.teledyneflir.com