

AS-PRIMER-A (Non FAA-PMA Product)

Product Description:

AS-PRIMER-A is a primer specially developed for use with Aerospace Sealants Silicone RTV products. It is used for improved adhesion to most metals, glass, plastic and composites.

Product Features:

- For use with Aerospace Sealants Silicone RTV products.
- Non-flammable

Typical Applications:

For use with Aerospace Sealants Silicone RTV products only to improve surface adhesion.

Color:

Light Pink

Chemical Cure System:

N/A

Limitations:

Use only as instructed. For use with Aerospace Sealants Silicone RTV products only. May not be compatible with other brands of Silicone RTV.

Handling and Safety

For maximum shelf life, keep containers sealed when not in use. Keep out of the reach of children. Refer to the SDS.

Shelf-life:

Sealed containers 1 year when stored in a cool dry area.

Primer for Aerospace Sealants Silicone RTV products

Typical Properties:

Viscosity, cps	5-15
Specific Gravity	.89
Consistency	Water
Tack Free Time, mins. @ R.T.	15

Method of Application:

Degrease all surfaces to which the primer and silicone rubber are to be applied. Allow the surface to dry or wipe dry with a clean, lint-free rag.

If applying by brush, apply sparingly. Apply primer to the degreased dry surface to be bonded using single light applications. Material will appear to be heavier in locations.

If possible, avoid multiple applications. After sufficient surface coverage has been achieved, close the primer container or replace the cover.

Leave primed articles to dry and cure for between 20 and 40 minutes depending on ambient temperature conditions.

Packaging:

Available in standard 0.5 fl oz. vials and 1.0 fl oz. vials (other size packaging available upon request).